## **Product Information Sheet**

COMMISSION DELEGATED REGULATION (EU) 2019/2015 with regard to energy labelling of light sources

Supplier's name or trade mark: Deko-Light

Supplier's address: Product Management, Deko-Light Elektronik Vertriebs GmbH, Auf der Hub 2,

D-76307 Karlsbad, DE

Model identifier: 565128

Type	of lig	ht s	ource:
------	--------	------	--------

Lighting technology used:	LED	Non-directional or directional:	DLS		
Light source cap-type	other electrical				
(or other electric interface)					
Mains or non-mains:	NMLS	Connected light source (CLS):	Nein		
Colour-tuneable light source:	Nein	Envelope:	-		
High luminance light source:	Nein				
Anti-glare shield:	Nein	Dimmable:	Only with specific dimmers		
Double to the control of					

## **Product parameters**

	•									
Parameter	Value	Parameter	Value							
General product parameters:										
Energy consumption in on- mode (kWh/1000 h), rounded up to the nearest integer	3	Energy efficiency class	G							
Useful luminous flux (φuse), indicating if it refers to the flux in a sphere (360°), in a wide cone (120°) or in a narrow cone (90°)	110 in Wide cone (120°)	Correlated colour temperature, rounded to the nearest 100 K, or the range of correlated colour temperatures, rounded to the nearest 100 K, that can be set	3 000							
On-mode power (P <sub>on</sub> ), expressed in W	2,0	Standby power (P <sub>sb</sub> ), expressed in W and rounded to the second decimal	0,00							
Networked standby power (P <sub>net</sub> ) for CLS, expressed in W and rounded to the second decimal	-	Colour rendering index, rounded to the nearest integer, or the range of CRI-values that can be set	80							

Outer	Height	18	Spectral power	See image		
dimensions	Width	70	distribution in the	in last page		
without separate control gear, lighting control parts and non- lighting control parts, if any (millimetre)	Depth	70	range 250 nm to 800 nm, at full-load			
Claim of equiva	lent power <sup>(a)</sup>	-	If yes, equivalent power (W)	-		
			Chromaticity	0,434		
			coordinates (x and y)	0,403		
Parameters for directional light sources:						
Peak luminous i	ntensity (cd)	38	Beam angle in degrees, or the range of beam angles that can be set	109		
Parameters for LED and OLED light sources:						
R9 colour rende	ring index value	0	Survival factor	0,90		
the lumen main	tenance factor	0,70				

(a)'-': not applicable; (b)'-': not applicable;

