## **Product Information Sheet**

COMMISSION DELEGATED REGULATION (EU) 2019/2015 with regard to energy labelling of light sources

Supplier's name or trade mark: Deko-Light

Supplier's address: Product Management, Deko-Light Elektronik Vertriebs GmbH, Auf der Hub 2,

D-76307 Karlsbad, DE

Model identifier: 565220

Type of light source:	Type	of light	source:
-----------------------	------	----------	---------

Lighting technology used:	LED	Non-directional or	DLS	
		directional:		
Light source cap-type	other electrical			
(or other electric interface)				
Mains or non-mains:	NMLS	Connected light	Nein	
		source (CLS):		
Colour-tuneable light source:	Nein	Envelope:	-	
High luminance light source:	Nein			
Anti-glare shield:	Nein	Dimmable:	Only with	
			specific dimmers	
Droduct parameters				

## **Product parameters**

Parameter	Value	Parameter	Value			
General product parameters:						
Energy consumption in on- mode (kWh/1000 h), rounded up to the nearest integer	25	Energy efficiency class	G			
Useful luminous flux (фuse), indicating if it refers to the flux in a sphere (360°), in a wide cone (120°) or in a narrow cone (90°)	2 500 in Wide cone (120°)	Correlated colour temperature, rounded to the nearest 100 K, or the range of correlated colour temperatures, rounded to the nearest 100 K, that can be set	3 000			
On-mode power (P <sub>on</sub> ), expressed in W	25,0	Standby power (P <sub>sb</sub> ), expressed in W and rounded to the second decimal	0,00			
Networked standby power (P <sub>net</sub> ) for CLS, expressed in W and rounded to the second decimal	-	Colour rendering index, rounded to the nearest integer, or the range of CRI-values that can be set	80			

Outer	Height	10	Spectral power	See image
dimensions	Width	295	distribution in the	in last page
without	Depth	295	range 250 nm to 800	
separate			nm, at full-load	
control gear,				
lighting				
control parts				
and non-				
lighting				
control parts,				
if any				
(millimetre)				
Claim of equivalent power <sup>(a)</sup>		-	If yes, equivalent	-
			power (W)	
			Chromaticity	0,434
			coordinates (x and y)	0,403
Parameters for directional light sources:				
Peak luminous i	ntensity (cd)	861	Beam angle in	114
			degrees, or the	
			range of beam	
			angles that can be	
			set	
Parameters for LED and OLED light sources:				
R9 colour rende	ring index value	-12	Survival factor	0,90
the lumen main	tenance factor	0,70		

(a)'-': not applicable; (b)'-': not applicable;

