# **Product Information Sheet**

COMMISSION DELEGATED REGULATION (EU) 2019/2015 with regard to energy labelling of light sources

#### Supplier's name or trade mark: Deko-Light

Supplier's address: -

### Model identifier: 733008

## Type of light source:

Lighting technology used:	LED	Non-directional or directional:	NDLS
Light source cap-type	other electrical		
(or other electric interface)			
Mains or non-mains:	MLS	Connected light source (CLS):	Nein
Colour-tuneable light source:	Nein	Envelope:	-
High luminance light source:	Nein		
Anti-glare shield:	Nein	Dimmable:	Only with specific dimmers

#### **Product parameters**

Parameter		Value	Parameter	Value		
General product parameters:						
Energy consur mode (kWh/10 up to the neare	00 h), rounded	7	Energy efficiency class	G		
indicating if it r in a sphere (3	us flux (фuse), efers to the flux 60º), in a wide n a narrow cone	290 in Sphere (360°)	Correlated colour temperature, rounded to the nearest 100 K, or the range of correlated colour temperatures, rounded to the nearest 100 K, that can be set	3 000		
On-mode p expressed in W	oower (P <sub>on</sub> ),	6,5	Standby power (P <sub>sb</sub> ), expressed in W and rounded to the second decimal	0,00		
for CLS, expre	ndby power (P <sub>net</sub> ) ssed in W and second decimal	-	Colour rendering index, rounded to the nearest integer, or the range of CRI- values that can be set	80		
Outer dimensions	Height	800	Spectral power distribution in the	See image in last page		
	Width	70		Seite 1/3		

without separate control gear, lighting control parts and non- lighting control parts, if any (millimetre)	Depth	70	range 250 nm to 800 nm, at full-load				
Claim of equival	ent power <sup>(a)</sup>	-	lf yes, equivalent power (W)	-			
			Chromaticity coordinates (x and y)	0,434 0,403			
Parameters for LED and OLED light sources:							
R9 colour rende	ring index value	3	Survival factor	0,90			
the lumen main	tenance factor	0,70					
Parameters for	LED and OLED ma	ains light sources:					
displacement fa	ctor (cos φ1)	0,80	Colour consistency in McAdam ellipses	6			
source replaces	an LED light s a fluorescent hout integrated icular wattage.	_(b)	lf yes then replacement claim (W)	-			
Flicker metric (P	est LM)	0,9	Stroboscopic effect metric (SVM)	3,5			

(a)'-' : not applicable;

(b)'-' : not applicable;

