## **Product Information Sheet**

COMMISSION DELEGATED REGULATION (EU) 2019/2015 with regard to energy labelling of light sources

sources					
Supplier's name	e or trade mark:	Magic Pyramid Brüd	cher & Partner KG		
Supplier's addr	ess: Info, Europa	allee 34, 50226 Fred	then, DE		
Model identifie	er: 127-647-24V				
Type of light so	urce:				
Lighting technology used:		LED	Non-directional or directional:	DLS	
Light source cap-type (or other electric interface)		2216 SMD			
Mains or non-mains:		NMLS	Connected light source (CLS):	Nein	
Colour-tuneable	e light source:	Nein	Envelope:	-	
High luminance light source:		Nein			
Anti-glare shield:		Nein	Dimmable:	Yes	
		Product para			
Parameter		Value	Parameter	Value	
		General product p			
Energy consumption in on- mode (kWh/1000 h), rounded up to the nearest integer		48	Energy efficiency class	G	
Useful luminous flux (фuse), indicating if it refers to the flux in a sphere (360°), in a wide cone (120°) or in a narrow cone (90°)		3 400 in Wide cone (120°)	Correlated colour temperature, rounded to the nearest 100 K, or the range of correlated colour temperatures, rounded to the nearest 100 K, that can be set	2 500	
On-mode power (P <sub>on</sub> ), expressed in W		48,0	Standby power (P <sub>sb</sub> ), expressed in W and rounded to the second decimal	0,00	
Networked standby power (P <sub>net</sub> ) for CLS, expressed in W and rounded to the second decimal		-	Colour rendering index, rounded to the nearest integer, or the range of CRI-values that can be set	90	
Outer	Height	2	Spectral power	See image	
dimensions without	Width	8	distribution in the	in last page	
without	Depth	5 000			

separate control gear, lighting control parts and non- lighting control parts, if any (millimetre)		range 250 nm to 800 nm, at full-load				
Claim of equivalent power <sup>(a)</sup>	-	If yes, equivalent power (W)	-			
		Chromaticity	0,477			
		coordinates (x and y)	0,413			
Parameters for directional light sources:						
Peak luminous intensity (cd)	1 082	Beam angle in degrees, or the range of beam angles that can be set	120			
Parameters for LED and OLED light sources:						
R9 colour rendering index value	-	Survival factor	-			
		_				

(a)'-': not applicable; (b)'-': not applicable;