Product Information Sheet


COMMISSION DELEGATED REGULATION (EU) 2019/2015 with regard to energy labelling of light sources

sources						
Supplier's name	e or trade mark:	Magic Pyramid Brüd	cher & Partner KG			
Supplier's addr	ess: Info, Europa	allee 34, 50226 Fred	chen, DE			
Model identifie	er: 127-648-24V					
Type of light so	urce:					
Lighting techno	logy used:	LED	Non-directional or directional:	DLS		
Light source cap-type (or other electric interface)		2216 SMD				
Mains or non-mains:		NMLS	Connected light source (CLS):	Nein		
Colour-tuneable	e light source:	Nein	Envelope:	-		
High luminance	light source:	Nein				
Anti-glare shield:		Nein	Dimmable:	Yes		
Product parameters						
Parameter		Value	Parameter	Value		
F		General product p				
Energy consumption in on- mode (kWh/1000 h), rounded up to the nearest integer		48	Energy efficiency class	G		
Useful luminous flux (фuse), indicating if it refers to the flux in a sphere (360°), in a wide cone (120°) or in a narrow cone (90°)		3 600 in Wide cone (120°)	Correlated colour temperature, rounded to the nearest 100 K, or the range of correlated colour temperatures, rounded to the nearest 100 K, that can be set	3 000		
On-mode power (P _{on}), expressed in W		48,0	Standby power (P _{sb}), expressed in W and rounded to the second decimal	0,00		
Networked standby power (P _{net}) for CLS, expressed in W and rounded to the second decimal		-	Colour rendering index, rounded to the nearest integer, or the range of CRI-values that can be set	90		
Outer	Height	2	Spectral power	See image		
dimensions without	Width	8	distribution in the	in last page		
without	Depth	5 000				

separate control gear, lighting control parts and non- lighting control parts, if any (millimetre)		range 250 nm to 800 nm, at full-load				
Claim of equivalent power ^(a)	-	If yes, equivalent power (W)	-			
		Chromaticity	0,436			
		coordinates (x and y)	0,404			
Parameters for directional light sources:						
Peak luminous intensity (cd)	1 146	Beam angle in	120			
		degrees, or the				
		range of beam				
		angles that can be				
		set				
Parameters for LED and OLED light sources:						
R9 colour rendering index value	68	Survival factor	-			
the lumen maintenance factor	-					

(a)_{'-'}: not applicable; (b)_{'-'}: not applicable;

Spectrum



Spectral Distribution