

2024-3-19 | Data subject to change without notice



Reflector Downlight | Black | Ø95mm | 60° | 3-CCT | 5~8W

Article number: 136-450

Due to the pre-settable light color and wattage, this downlight is suitable for placement in various areas such as offices, living areas, schools, hotels and other public spaces.

Features

- Available in six different sizes;
- Color temperature adjustable by CCT switch (3000K, 4000K and 5700K);
- Included driver adjustable in 5, 5.5, 6, 7 and 8 watts;
- IP20 for indoor use (IP54 when mounted).

Specifications

Type	Round	Driver	Incl. external non-dimmable driver	Cable length	120 cm
Input voltage	230V	Power factor	>0.90	Connection type	Europlug
Power	5/5.5/6/7/8 Watt	Beam angle	60°	Housing material	Aluminium
Luminous flux	550 Lm	Adjustable	No	Housing color	Black
Color temperature	3-CCT	IP rate	IP20 (IP54 when mounted)	Material cover	PC
Light color	Warm white, natural white and cold white (3000K, 4000K en 5700K)	Mounting	Recessed	Certification mark	CE, RoHS
Dimming method	Optional	Diameter	Ø 95 mm	Warranty	5 years
Lifetime	L70B50 (40.000 hours)	Mounting hole	Ø 82 mm		
CRI value	>80	Mounting depth	55 mm		

