

2024-3-19 | Data subject to change without notice



Reflector Downlight | Black | Ø172mm | 60° | 3-CCT | 6~15W

Article number: 136-453

Due to the pre-settable light color and wattage, this downlight is suitable for placement in various areas such as offices, living areas, schools, hotels and other public spaces.

Features

- Available in six different sizes;
- Color temperature adjustable by CCT switch (3000K, 4000K and 5700K);
- Included driver adjustable in 6, 8, 10, 13 and 15 watts;
- IP20 for indoor use (IP54 when mounted).

Specifications

Type	Round	Driver	Incl. external	Cable length	120 cm
Input voltage	230V		dimmable driver	Connection type	Europlug
Power	6/8/10/13/15 Watt	Power factor	>0.90	Housing material	Aluminium
Luminous flux	1640 Lm	Beam angle	60°	Housing color	Black
Color temperature	3-CCT	Adjustable	No	material cover	PC
Light color	Warm white, natural white and cold white (3000K, 4000K en 5700K)	IP rate	IP20 (IP54 when mounted)	Certification mark	CE, RoHS
		Mounting	Recessed	Warranty	5 years
Dimming method	Optional	Diameter	Ø 172 mm		
Lifetime	L70B50 (40.000 hours)	Mounting hole	Ø 150 mm		
CRI value	>80	Mounting depth	90 mm		

