

2021-9-10 | Data subject to change without notice

Panel | 30*120 | >100Lm/W | 4000K |
White Frame | Non Dim.

Article number: 174-154



This LED panel is suitable for installation in (suspended) ceilings of 30x120 cm. A hanging up method is also possible, using suspension cables or a surface mounting kit (see related products). The smooth, soft and flicker-free light spread by the LED panel, makes it extremely suitable for use in offices and retail spaces, but also think of indoor lighting of schools and any other public spaces.

Features

- High quality external driver with optimum heat regulation
- Flicker-free (1%)
- Plug & Play due connection cable and euro plug
- High light efficiency of >100 Lm/W
- 5 year warranty
- Also available with a dimmable Dali, 1-10V or Triac LED driver

Specifications

| | | | | | |
|---------------------|-----------------------|--------------|---|--------------------|--------------------------------|
| Size | 30 x 120 cm | CRI value | >80 | Height | 11 mm |
| Input voltage | 220-240V | UGR value | UGR>19 | Cable length | 200 cm |
| Power | 36 Watt | Driver | Incl. external driver (not dimmable) | Connection type | Europlug |
| Luminous flux | 3600 Lm | Power factor | >0.97 | Housing material | Aluminium |
| Luminous efficiency | >100 Lm/W | Flicker-free | Yes 1% | Housing color | White (powder coating) |
| Color temperature | 4000K | Beam angle | 120° | Material diffuser | PMMA (Polymethyl methacrylate) |
| Light color | Natural white | IP rate | IP20 | Lighting method | Edge-lit |
| Dimming method | Not dimmable | Length | 1195 mm | Certification mark | CE, RoHS |
| Lifetime | L80B50 (50.000 hours) | Width | 295 mm | Warranty | 5 years |



Line Drawings



