



## Panel | 60\*60 | >100Lm/W | 6000K | White Frame | Dali Dim.

Article number: 174-187

This LED panel is suitable for installation in (suspended) ceilings of 60x60 cm. A hanging up method is also possible, using suspension cables or a surface mounting kit. The smooth, soft and flicker-free light spread by the LED panel, makes it extremely suitable for use in offices and retail spaces, but also think of indoor lighting of schools and any other public spaces.

### Features

- High quality external Dali dimmable driver with optimum heat regulation
- Flicker-free (1%)
- Plug & Play due connection cable and euro plug
- High light efficiency of >100 Lm/W
- 5 year warranty
- Also available with a dimmable Triac or 1-10V LED driver

## Specifications

|                     |                       |              |                       |                    |                                |
|---------------------|-----------------------|--------------|-----------------------|--------------------|--------------------------------|
| Size                | 60 x 60 cm            | CRI value    | >80                   | Height             | 11 mm                          |
| Input voltage       | 220-240V              | UGR value    | UGR>19                | Cable length       | 100 cm                         |
| Power               | 36 Watt               | Driver       | Incl. external driver | Connection type    | Europlug                       |
| Luminous flux       | 3600 Lm               | Power factor | >0.97                 | Housing material   | Aluminium                      |
| Luminous efficiency | >100 Lm/W             | Flicker-free | Yes 1%                | Housing color      | White (powder coating)         |
| Color temperature   | 6000K                 | Beam angle   | 120°                  | Material diffuser  | PMMA (Polymethyl methacrylate) |
| Light color         | Cold white            | IP rate      | IP20                  | Lighting method    | Edge-lit                       |
| Dimming method      | Dali                  | Length       | 595 mm                | Certification mark | CE, RoHS                       |
| Lifetime            | L80B50 (50.000 hours) | Width        | 595 mm                | Warranty           | 5 years                        |



## Line Drawings



