

2021-9-10 | Data subject to change without notice



Panel | Ø61cm | 40W | 3000K | CRI>90 | UGR<19 | Non Dim.

Article number: 174-204

This round LED panel comes with a suspension set and driverbox. This suspension set makes it possible to attach the panel to the ceiling with a maximum height of 130 cm. Due to the smooth, soft and flicker-free light that the LED panel spreads, panels are ideally suited for use in offices and shops, but also for interior lighting in schools and other public spaces.

Features

- High quality external driver with optimal heat regulation
- Flicker-free (1%)
- High light efficiency of >100 Lm/W
- 5 years warranty
- CRI > 90
- UGR <19 value for minimal discomfort from glare and high productivity
- Suspension set and driver box included

Specifications

Size	Ø61 cm	CRI value	>90	Cable length	N/a
Input voltage	220-240V	UGR value	UGR<19	Connection type	Terminal block
Power	40 Watt	Driver	Incl. external driver (not dimmable)	Housing material	Aluminium
Luminous flux	4277 Lm	Power factor	>0.90	Housing color	White (powder coating)
Luminous efficiency	>100 Lm/W	Flicker-free	Yes 1%	Material diffuser	PMMA (Polymethyl methacrylate)
Color temperature	3000K	Beam angle	90°	Lighting method	Edge-lit
Light color	Warm white	IP rate	IP20	Certification mark	CE, RoHS
Dimming method	Not dimmable	Diameter	Ø 610 mm	Warranty	5 years
Lifetime	L80B50 (44.000 hours)	Height	15 mm, height suspension cable max. 130 cm		



Line Drawings



