



Panel | Ø61cm | 40W | 4000K |
CRI>90 | UGR<19 | Non Dim.

Article number: 174-205

This round LED panel comes with a suspension set and driverbox. This suspension set makes it possible to attach the panel to the ceiling with a maximum height of 130 cm. Due to the smooth, soft and flicker-free light that the LED panel spreads, panels are ideally suited for use in offices and shops, but also for interior lighting in schools and other public spaces.

Features

- High quality external driver with optimal heat regulation
- Flicker-free (1%)
- High light efficiency of >100 Lm/W
- 5 years warranty
- CRI> 90
- UGR <19 value for minimal discomfort from glare and high productivity
- Suspension set and driver box included

Specifications

| | | | | | |
|---------------------|-----------------------|--------------|---|--------------------|--------------------------------|
| Size | Ø61 cm | CRI value | >90 | Cable length | N/a |
| Input voltage | 220-240V | UGR value | UGR<19 | Connection type | Terminal block |
| Power | 40 Watt | Driver | Incl. external driver | Housing material | Aluminium |
| Luminous flux | 4277 Lm | | (not dimmable) | Housing color | White (powder coating) |
| Luminous efficiency | >100 Lm/W | Power factor | >0.90 | Material diffuser | PMMA (Polymethyl methacrylate) |
| Color temperature | 4000K | Flicker-free | Yes 1% | Lighting method | Edge-lit |
| Light color | Natural white | Beam angle | 90° | Certification mark | CE, RoHS |
| Dimming method | Not dimmable | IP rate | IP20 | Warranty | 5 years |
| Lifetime | L80B50 (44.000 hours) | Diameter | Ø 610 mm | | |
| | | Height | 15 mm. Height suspension cables max. 130 cm | | |



Line Drawings



