

## Panel Square ECO | Cut Out 105\*105mm | 4000K | 6 Watt

Article number: 174-321



There was a growing need from the market for a "low entry" Downlight. Our answer presented itself in the form of the "Tronix ECO Downlight series".

In other words, a price-accessible series of professional Downlights that is not inferior to the upper models in price-quality ratio, but in terms of specifications has been stripped down to an even more favorable package of specifications.

For example, a slightly lower Lm/W output and an internal instead of external driver.

### Features

Non dimmable internal driver

Available in various sizes or Power

## Specifications

Type	Square	Driver	Incl. internal driver	Cable length	20 cm
Input voltage	220-240V	Power factor	>0.50	Connection type	Stripped wire
Power	6 Watt	Beam angle	120°	Housing material	PC
Luminous flux	390 Lm	Adjustable	No	Housing color	White
Color temperature	3000K	IP rate	IP44	material cover	PC
Light color	Natural white	Mounting	Recessed	Color cover	White
Dimming method	Not dimmable	Diameter	115 x 115 mm	Certification mark	CE, RoHS
Lifetime	L70B50 (30.000 hours)	Mounting hole	105 x 105 mm	Warranty	3 years
CRI value	>80	Mounting depth	30 mm		



## Line Drawings

