

CANON K-35 LENS REHOUSING

FULL FRAME HIGHSPEED CINE LENSES

P+S TECHNIK
Optics for Exceptional Images

This P+S TECHNIK rehousing transforms full frame Canon K-35 stills lenses into fully functional cine lenses. The new housing includes new internal mechanics for focus and iris and standard PL mount. Exchange mounts are available.

Aperture and focus gear rings are in the same distance throughout the series. Focus rings are available in meter or feet. A Canon K-35 lens set can be completed very well with the Canon FD focal lengths of 14 mm, 100 mm, 135 mm and 200 mm.



WWW.PSTECHNIK.DE



Canon K-35 Lens Rehousing

Technical Specifications

Model	Canon K-35					
Focal Length	18 mm	24 mm	35 mm	50 mm	55 mm	85 mm
T-Stop	T1.5	T1.5	T1.3	T1.3	T1.3	T1.4
Angular Rotation of Iris Scale	85°	85°	85°	tbd	75°	75°
Close Focus	0,3 m / 12 in	0,3 m / 12 in	0,3 m / 12 in	0,5 m / 20 in	0,6 m / 24 in	0,9 m / 3 ft
Angular Rotation to MOD	270°	270°	270°	270°	270°	270°
Image Circle	43 mm	43 mm	43 mm	43 mm	43 mm	43 mm
Mount	PL, IMS Interchangeable Mount System					
Front Diameter	110 mm					
Weight	1.400.gr.	1.200.gr.	1.600.gr.	1.400.gr.	1.600.gr.	1.600.gr.

