



ENGINE STOP LEAK BARD AHL

Safety Data Sheet

according to Regulation (EC) No. 1907/2006 (REACH) with its amendment Regulation (EU) 2015/830

Date of issue: 21-08-15 Version: 1.0

SECTION 1: Identification of the substance/mixture and of the company/undertaking

1.1. Product identifier

Product form : Mixture
Product name : ENGINE STOP LEAK BARD AHL
Product code : 1107B # 737110RR2
Type of product : Lubricants and additives

1.2. Relevant identified uses of the substance or mixture and uses advised against

1.2.1. Relevant identified uses

Intended for general public
Main use category : Consumer use
Function or use category : Lubricants and additives

1.2.2. Uses advised against

No additional information available

1.3. Details of the supplier of the safety data sheet

SADAPS BARD AHL Additives & Lubricants
ZI TOURNAI OUEST 2 - RUE DU MONT DES CARLIERS, 3
7522 TOURNAI - BELGIQUE
T +32 (0).69.59.03.60 - F +32 (0).69.59.03.61
msds@bardahlfrance.com - www.bardahlfrance.com

1.4. Emergency telephone number

Emergency number : + 32 (0)70.245.245 / +33 (0)1.45.42.59.59

Country	Organisation/Company	Address	Emergency number	Comment
Greece	Poisons Information Centre Children's Hospital "Aglaia. Kyriakou"	11527 Athens	+30 10 779 3777	
Malta	Medicines & Poisons Info Office	Mater Dei Hospital MSD Msida	+356 2545 6504	
United Kingdom	National Poisons Information Service (Belfast Centre) Royal Victoria Hospital	Grosvenor Road BT12 6BA Belfast	0844 892 0111 (UK only, Monday to Friday, 08.00 to 18.00 hours)	

SECTION 2: Hazards identification

2.1. Classification of the substance or mixture

Classification according to Regulation (EC) No. 1272/2008 [CLP]

Not classified

Adverse physicochemical, human health and environmental effects

No additional information available

2.2. Label elements

Labelling according to Regulation (EC) No. 1272/2008 [CLP]

Precautionary statements (CLP) : P101 - If medical advice is needed, have product container or label at hand
P102 - Keep out of reach of children
P301+P310 - IF SWALLOWED: Immediately call a POISON CENTER, a doctor
P501 - Dispose of contents/container in accordance with local regulations
EUH-statements : EUH208 - Contains Calcium long chain alkaryl sulphonate.. May produce an allergic reaction

2.3. Other hazards

Other hazards not contributing to the classification : Note L : The classification as a carcinogen need not apply if it can be shown that the substance contains less than 3 % DMSO extract as measured by IP 346 'Determination of polycyclic aromatics in unused lubricating base oils and asphaltene free petroleum fractions — Dimethyl sulphoxide extraction refractive index method', Institute of Petroleum, London. This note applies only to certain complex oil-derived substances in Part 3.

ENGINE STOP LEAK BARDAHL

Safety Data Sheet

according to Regulation (EC) No. 1907/2006 (REACH) with its amendment Regulation (EU) 2015/830

SECTION 3: Composition/information on ingredients

3.1. Substance

Not applicable

3.2. Mixture

Name	Product identifier	%	Classification according to Regulation (EC) No. 1272/2008 [CLP]
Xylene	(CAS No) 1330-20-7 (EC no) 215-535-7 (EC index no) 601-022-00-9 (REACH-no) 01-2119488216-32	<5	Flam. Liq. 3, H226 Acute Tox. 4 (Inhalation), H332 Acute Tox. 4 (Dermal), H312 Skin Irrit. 2, H315
Polyolefin polyamine succinimide, polyol	(EC no) polymer	<3	Aquatic Chronic 4, H413
ethylbenzene	(CAS No) 100-41-4 (EC no) 202-849-4 (EC index no) 601-023-00-4	<3	Flam. Liq. 2, H225 Acute Tox. 4 (Inhalation:vapour), H332

Full text of H-statements: see section 16

SECTION 4: First aid measures

4.1. Description of first aid measures

First-aid measures general	: Never give anything by mouth to an unconscious person. If medical advice is needed, have product container or label at hand.
First-aid measures after inhalation	: If breathing is difficult, remove victim to fresh air and keep at rest in a position comfortable for breathing.
First-aid measures after skin contact	: Remove contaminated clothes. Wash skin with plenty of water. Wash contaminated clothing before reuse.
First-aid measures after eye contact	: IF IN EYES: Rinse cautiously with water for several minutes. Remove contact lenses, if present and easy to do. Continue rinsing.
First-aid measures after ingestion	: Do NOT induce vomiting. Immediately call a POISON CENTER or doctor/physician.

4.2. Most important symptoms and effects, both acute and delayed

Symptoms/injuries after skin contact : May produce an allergic reaction.

4.3. Indication of any immediate medical attention and special treatment needed

Treat symptomatically.

SECTION 5: Firefighting measures

5.1. Extinguishing media

Suitable extinguishing media	: Carbon dioxide. Dry powder. Sand.
Unsuitable extinguishing media	: Do not use a heavy water stream.

5.2. Special hazards arising from the substance or mixture

Hazardous decomposition products in case of fire : Incomplete combustion releases dangerous carbon monoxide, carbon dioxide and other toxic gases.

5.3. Advice for firefighters

Firefighting instructions	: Exercise caution when fighting any chemical fire.
Protection during firefighting	: Do not enter fire area without proper protective equipment, including respiratory protection.
Other information	: Prevent liquid from entering sewers, watercourses, underground or low areas.

SECTION 6: Accidental release measures

6.1. Personal precautions, protective equipment and emergency procedures

General measures : Evacuate area. Eliminate every possible source of ignition. Ensure adequate ventilation, especially in confined areas. Spill area may be slippery. Keep public away from danger area. Equip cleanup crew with proper protection.

6.1.1. For non-emergency personnel

No additional information available

6.1.2. For emergency responders

No additional information available

6.2. Environmental precautions

Dike for recovery or absorb with appropriate material. Prevent entry to sewers and public waters. Notify authorities if liquid enters sewers or public waters.

ENGINE STOP LEAK BARDAHL

Safety Data Sheet

according to Regulation (EC) No. 1907/2006 (REACH) with its amendment Regulation (EU) 2015/830

6.3. Methods and material for containment and cleaning up

For containment	: Recover the product with absorbent material.
Methods for cleaning up	: Clean up any spills as soon as possible, using an absorbent material to collect it.
Other information	: Spill area may be slippery.

6.4. Reference to other sections

For further information refer to section 8: "Exposure controls/personal protection". For disposal of solid materials or residues refer to section 13: "Disposal considerations".

SECTION 7: Handling and storage

7.1. Precautions for safe handling

Precautions for safe handling	: Do not eat, drink or smoke when using this product.
Hygiene measures	: Wash contaminated clothing before reuse. Always wash hands after handling the product.

7.2. Conditions for safe storage, including any incompatibilities

Storage conditions	: Store in a dry place. Store in a closed container. Store in a well-ventilated place. Keep out of frost. Keep away from heat.
Maximum storage period	: 60 months

7.3. Specific end use(s)

No additional information available

SECTION 8: Exposure controls/personal protection

8.1. Control parameters

PPG-2 METHYL ETHER (34590-94-8)		
France	VME (mg/m ³)	308 mg/m ³
France	VME (ppm)	50 ppm
Oil mist		
France	VME (mg/m ³)	5 mg/m ³
France	VLE (mg/m ³)	10 mg/m ³
Xylene (1330-20-7)		
EU	IOELV TWA (mg/m ³)	221 mg/m ³
EU	IOELV TWA (ppm)	50 ppm
EU	IOELV STEL (mg/m ³)	442 mg/m ³
EU	IOELV STEL (ppm)	100 ppm
Belgium	Limit value (mg/m ³)	221 mg/m ³
Belgium	Limit value (ppm)	50 ppm
Belgium	Short time value (mg/m ³)	100 mg/m ³
Belgium	Short time value (ppm)	442 ppm
France	VME (mg/m ³)	221 mg/m ³
France	VME (ppm)	50 ppm
France	VLE (mg/m ³)	442 mg/m ³
France	VLE (ppm)	100 ppm
ethylbenzene (100-41-4)		
Belgium	Limit value (mg/m ³)	440 mg/m ³
Belgium	Limit value (ppm)	100 ppm
Belgium	Short time value (mg/m ³)	551 mg/m ³
Belgium	Short time value (ppm)	125 ppm
Distillates (petroleum), solvent-dewaxed heavy paraffinic (64742-65-0)		
France	VME (mg/m ³)	7 (8h)
France	VME (ppm)	5 ppm (8h)
France	VLE (mg/m ³)	14 mg/m ³ (15m)
France	VLE (ppm)	10 ppm (15m)

8.2. Exposure controls

Hand protection:

Protective gloves

Type	Material	Permeation	Thickness (mm)	Penetration	Standard
Disposable gloves, Reusable gloves	Nitrile rubber (NBR)	6 (> 480 minutes)		3 (> 0.65)	EN 374

ENGINE STOP LEAK BARDAHL

Safety Data Sheet

according to Regulation (EC) No. 1907/2006 (REACH) with its amendment Regulation (EU) 2015/830

Eye protection:

Eye protection should only be necessary where liquid could be splashed or sprayed

Skin and body protection:

Wear suitable protective clothing

Respiratory protection:

Good ventilation of the workplace required



SECTION 9: Physical and chemical properties

9.1. Information on basic physical and chemical properties

Physical state	: Liquid
Appearance	: Oily. clear.
Colour	: red.
Odour	: No data available
Odour threshold	: No data available
pH	: No data available
Relative evaporation rate (butylacetate=1)	: No data available
Melting point	: No data available
Freezing point	: No data available
Boiling point	: No data available
Flash point	: 65 °C
Auto-ignition temperature	: No data available
Decomposition temperature	: No data available
Flammability (solid, gas)	: No data available
Vapour pressure	: No data available
Relative vapour density at 20 °C	: No data available
Relative density	: No data available
Density	: 0,875 - 0,885 g/cm ³ 20°C
Solubility	: No data available
Log Pow	: No data available
Viscosity, kinematic	: No data available
Viscosity, dynamic	: No data available
Explosive properties	: No data available
Oxidising properties	: No data available
Explosive limits	: No data available

9.2. Other information

No additional information available

SECTION 10: Stability and reactivity

10.1. Reactivity

Stable under normal conditions of use.

10.2. Chemical stability

Stable under normal conditions.

10.3. Possibility of hazardous reactions

Not established.

10.4. Conditions to avoid

Heat. Open flame. Sparks. Water, humidity. Freezing.

10.5. Incompatible materials

No additional information available

ENGINE STOP LEAK BARD AHL

Safety Data Sheet

according to Regulation (EC) No. 1907/2006 (REACH) with its amendment Regulation (EU) 2015/830

10.6. Hazardous decomposition products

Incomplete combustion releases dangerous carbon monoxide, carbon dioxide and other toxic gases.

SECTION 11: Toxicological information

11.1. Information on toxicological effects

Acute toxicity : Not classified

PPG-2 METHYL ETHER (34590-94-8)	
LD50 oral rat	5135 mg/kg
LD50 dermal rabbit	9510 mg/kg
LC50 inhalation rat (mg/l)	3,35 mg/l

Xylene (1330-20-7)	
LD50 oral rat	4300 mg/kg
LC50 inhalation rat (mg/l)	28,1

ethylbenzene (100-41-4)	
LD50 oral rat	3500
LD50 dermal rabbit	5000

Distillates (petroleum), solvent-dewaxed heavy paraffinic (64742-65-0)	
LD50 oral rat	> 5000 mg/kg
LD50 dermal rabbit	> 5000 mg/kg
LC50 inhalation rat (Dust/Mist - mg/l/4h)	5,53 mg/l/4h

Skin corrosion/irritation : Not classified

Serious eye damage/irritation : Not classified

Respiratory or skin sensitisation : Not classified

Germ cell mutagenicity : Not classified

Carcinogenicity : < 3% DMSO (IP 346)

Reproductive toxicity : Not classified

Specific target organ toxicity (single exposure) : Not classified

Specific target organ toxicity (repeated exposure) : Not classified

Aspiration hazard : Not classified

SECTION 12: Ecological information

12.1. Toxicity

PPG-2 METHYL ETHER (34590-94-8)	
LC50 fish 1	> 1000 mg/l
EC50 Daphnia 1	1919 mg/l

Xylene (1330-20-7)	
LC50 fish 1	2,6 mg/l (Onchorhyncus mykiss)
EC50 Daphnia 1	1 ml/l
NOEC (chronic)	> 1,3 mg/l

ethylbenzene (100-41-4)	
LC50 fish 1	4,2 mg/l

12.2. Persistence and degradability

PPG-2 METHYL ETHER (34590-94-8)	
Biodegradation	75 %

Xylene (1330-20-7)	
Persistence and degradability	Readily biodegradable.
BOD (% of ThOD)	84 % ThOD (10 days)

12.3. Bioaccumulative potential

PPG-2 METHYL ETHER (34590-94-8)	
Log Pow	1,01

Distillates (petroleum), solvent-dewaxed heavy paraffinic (64742-65-0)	
Log Pow	> 3

ENGINE STOP LEAK BARDAHL

Safety Data Sheet

according to Regulation (EC) No. 1907/2006 (REACH) with its amendment Regulation (EU) 2015/830

12.4. Mobility in soil

No additional information available

12.5. Results of PBT and vPvB assessment

No additional information available

12.6. Other adverse effects

No additional information available

SECTION 13: Disposal considerations

13.1. Waste treatment methods

Sewage disposal recommendations : Do not discharge into drains or the environment.
Waste disposal recommendations : Collect all waste in suitable and labelled containers and dispose according to local legislation.
Ecology - waste materials : Do not discharge the product into the environment.

SECTION 14: Transport information

In accordance with ADR / RID / IMDG / IATA / ADN

ADR	IMDG	IATA	ADN	RID
14.1. UN number				
Not regulated	Not regulated	Not regulated	Not regulated	Not regulated
14.2. UN proper shipping name				
Not regulated	Not regulated	Not regulated	Not regulated	Not regulated
Not regulated	Not regulated	Not regulated	Not regulated	Not regulated
14.3. Transport hazard class(es)				
Not regulated	Not regulated	Not regulated	Not regulated	Not regulated
Not regulated	Not regulated	Not regulated	Not regulated	Not regulated
14.4. Packing group				
Not regulated	Not regulated	Not regulated	Not regulated	Not regulated
14.5. Environmental hazards				
Not regulated	Not regulated	Not regulated	Not regulated	Not regulated
No supplementary information available				

14.6. Special precautions for user

- Overland transport

Not regulated

- Transport by sea

Not regulated

- Air transport

Not regulated

- Inland waterway transport

Not regulated

- Rail transport

Not regulated

14.7. Transport in bulk according to Annex II of MARPOL and the IBC Code

Not applicable

SECTION 15: Regulatory information

15.1. Safety, health and environmental regulations/legislation specific for the substance or mixture

15.1.1. EU-Regulations

Contains no REACH substances with Annex XVII restrictions

Contains no substance on the REACH candidate list

Contains no REACH Annex XIV substances

15.1.2. National regulations

France

ENGINE STOP LEAK BARD AHL

Safety Data Sheet

according to Regulation (EC) No. 1907/2006 (REACH) with its amendment Regulation (EU) 2015/830

Occupational diseases : RG 36 - Affections provoquées par les huiles et graisses d'origine minérale ou de synthèse
RG 4 BIS - Affections gastro-intestinales provoquées par le benzène, le toluène, les xylènes et tous les produits en renfermant
RG 65 - Lésions eczématiformes de mécanisme allergique

Germany

VwVwS Annex reference : Water hazard class (WGK) 3, severe hazard to waters (Classification according to VwVwS, Annex 4)

12th Ordinance Implementing the Federal Immission Control Act - 12.BImSchV : Is not subject of the 12. BImSchV (Hazardous Incident Ordinance)

Netherlands

SZW-lijst van kankerverwekkende stoffen : None of the components are listed

SZW-lijst van mutagene stoffen : None of the components are listed

NIET-limitatieve lijst van voor de voortplanting giftige stoffen – Borstvoeding : None of the components are listed

NIET-limitatieve lijst van voor de voortplanting giftige stoffen – Vruchtbaarheid : None of the components are listed

NIET-limitatieve lijst van voor de voortplanting giftige stoffen – Ontwikkeling : Xylene is listed

Denmark

Class for fire hazard : Class III-1

Store unit : 50 liter

Classification remarks : Flammable according to the Danish Ministry of Justice; Emergency management guidelines for the storage of flammable liquids must be followed

Recommendations Danish Regulation : Pregnant/breastfeeding women working with the product must not be in direct contact with the product
The requirements from the Danish Working Environment Authorities regarding work with carcinogens must be followed during use and disposal

15.2. Chemical safety assessment

No additional information available

SECTION 16: Other information

Full text of H- and EUH-statements:

Acute Tox. 4 (Dermal)	Acute toxicity (dermal), Category 4
Acute Tox. 4 (Inhalation)	Acute toxicity (inhal.), Category 4
Acute Tox. 4 (Inhalation:vapour)	Acute toxicity (inhalation:vapour) Category 4
Aquatic Chronic 4	Hazardous to the aquatic environment — Chronic Hazard, Category 4
Flam. Liq. 2	Flammable liquids, Category 2
Flam. Liq. 3	Flammable liquids, Category 3
Skin Irrit. 2	Skin corrosion/irritation, Category 2
H225	Highly flammable liquid and vapour
H226	Flammable liquid and vapour
H312	Harmful in contact with skin
H315	Causes skin irritation
H332	Harmful if inhaled
H413	May cause long lasting harmful effects to aquatic life
EUH208	Contains . May produce an allergic reaction

SDS EU (REACH Annex II)

This information is based on our current knowledge and is intended to describe the product for the purposes of health, safety and environmental requirements only. It should not therefore be construed as guaranteeing any specific property of the product