

Attestation of Conformity

No. N8A 083334 0063 Rev. 00

Holder of Certificate: Ningbo Ulica Solar

Science & Technology Co., Ltd

No. 181, Shanshan Road Wangchun Industrial District

315177 Ningbo

PEOPLE'S REPUBLIC OF CHINA

Product:

Crystalline Silicon Terrestrial Photovoltaic (PV) Modules

Mono-Crystalline Silicon Photovoltaic Module

This Attestation of Conformity is issued on a voluntary basis according to the Low Voltage Directive 2014/35/EU relating to electrical equipment designed for use within certain voltage limits. It confirms that the listed equipment complies with the principal protection requirements of the directive and is based on the technical specifications applicable at the time of issuance.

It refers only to the particular sample submitted for testing and certification. See also notes overleaf.

Test report no.:

704061806602-04

Date.

2020-02-28

(Zhulin Zhang)

Dogo 1 of 2

After preparation of the necessary technical documentation as well as the EU declaration of conformity the required CE marking can be affixed on the product. The declaration of conformity is issued under the sole responsibility of the manufacturer. Other relevant EU-directives have to be observed.





Attestation of Conformity

No. N8A 083334 0063 Rev. 00

Model(s):

1000 V DC system voltage Single Glass modules: UL-xxxM-72, xxx= 330 to 390 in step of 5: UL-xxxM-60, xxx= 275 to 325 in step of 5; UL-xxxM-54, xxx= 245 to 290 in step of 5; UL-xxxM-48, xxx= 220 to 260 in step of 5; 1500 V DC system voltage Single Glass modules: UL-xxxM-72HV, xxx= 330 to 390 in step of 5; UL-xxxM-60HV, xxx= 275 to 325 in step of 5; UL-xxxM-54HV, xxx= 245 to 290 in step of 5; UL-xxxM-48HV, xxx= 220 to 260 in step of 5;

Half cell 1000 V DC system voltage Single Glass modules: UL-xxxM-144, xxx= 370 to 415 in step of 5; UL-xxxM-120, xxx= 305 to 345 in step of 5; UL-xxxM-108, xxx= 275 to 315 in step of 5; UL-xxxM-96, xxx= 245 to 275 in step of 5; UL-xxxM-144, xxx= 430 to 450 in step of 5; UL-xxxM-120, xxx= 360 to 375 in step of 5; UL-xxxM-108, xxx= 325 to 335 in step of 5; UL-xxxM-96, xxx= 290 to 300 in step of 5; Half cell 1500 V DC system voltage Single Glass modules: UL-xxxM-144HV, xxx= 370 to 415 in step of 5; UL-xxxM-120HV, xxx= 305 to 345 in step of 5; UL-xxxM-108HV, xxx= 275 to 315 in step of 5; UL-xxxM-96HV, xxx= 245 to 275 in step of 5: UL-xxxM-144HV, xxx= 430 to 450 in step of 5; UL-xxxM-120HV, xxx= 360 to 375 in step of 5; UL-xxxM-108HV, xxx= 325 to 335 in step of 5; UL-xxxM-96HV, xxx= 290 to 300 in step of 5; xxx is standing for rated output power at STC

Parameters:

Construction: Framed, with Junction box,

Cable and Connectors. Yangzhou Opto-Electrical

Test Laboratory: **Products Testing Institute**

No. 10 West Kaifa Road, Yangzhou

225009 Jiangsu, P. R. China

Safety Class: Class II

Maximum System Voltage:

Fire Safety Class:

1000 V DC or 1500 V DC

Class C according to UL790.

Tested according to: EN IEC 61730-1:2018

EN IEC 61730-1:2018/AC:2018-06

EN IEC 61730-2:2018

EN IEC 61730-2:2018/AC:2018-06

Page 2 of 2

After preparation of the necessary technical documentation as well as the EU declaration of conformity the required CE marking can be affixed on the product. The declaration of conformity is issued under the sole responsibility of the manufacturer. Other relevant EU-directives have to be observed.

