

Koaxialkabel

Anschlusskabel
1,5 m

Fte[®]
maximal



AKS 150 L



AKB 150 L



AKSS 150 L

Technische Daten AKS 150 L / AKB 150 L / AKSS 150 L



	AKS 150 L	AKB 150 L	AKSS 150 L
Art.-Nr.	0901069	0901066	0901072
Anschlüsse	F-Stecker / F-Stecker	90° IEC-Stecker / 90° IEC-Buchse	F-Stecker / IEC-Stecker
Länge	1.5 m	1.5 m	1.5 m
Innenleiter (mm) ø	1.0 Cu	1.0 Cu	1.0 Cu
Dielektrikum (mm) ø	4.6 PE	4.6 PE	4.6 PE
Folie	Al / Pet / Al	Al / Pet / Al	Al / Pet / Al
Schirmung Material	Al	Al	Al
Schirmung (Nr. der Drähte)	128	128	128
Zweite Folie	Al / Pet	Al / Pet	Al / Pet
Schirmungsmaß (30-900MHz)	> 110 dB	> 110 dB	> 110 dB
Außendurchmesser (mm) ø	7.06	7.06	7.06
Mantel Material	PVR weiß	PVR weiß	PVR weiß
Impedanz	75 Ohms	75 Ohms	75 Ohms
Art	3-fach Geschirmt	3-fach Geschirmt	3-fach Geschirmt
Dämpfungen (dB/100m)			
47 MHz	4.8	4.8	4.8
175 MHz	8.3	8.3	8.3
470 MHz	13.5	13.5	13.5
862 MHz	18.8	18.8	18.8
950 MHz	19.9	19.9	19.9
1350 MHz	24.0	24.0	24.0
1750 MHz	27.5	27.5	27.5
2150 MHz	30.9	30.9	30.9