

Safety Data Sheet**YJG009 Interdeck Sand Beige****Version No. 2 Date Last Revised 17/08/11**

Conforms to the requirements of Regulation (EC) No.1907/2006 (REACH), Annex II and Regulation (EC) No.1272/2008

SECTION 1: Identification of the substance/mixture and of the company/undertaking**1.1. Product identifier** Interdeck Sand Beige

Product Code YJG009

Registration Number

1.2. Relevant identified uses of the substance or mixture and uses advised against

Intended use See Technical Data Sheet.

For amateur use only.

Application Method See Technical Data Sheet.

1.3. Details of the supplier of the safety data sheet**Manufacturer** International Paint Ltd.

Stoneygate Lane

Felling Gateshead

Tyne and Wear

NE10 0JY UK

Telephone No. +44 (0)191 469 6111**Fax No.** +44 (0)191 438 3711**1.4. Emergency telephone number****Manufacturer** +44 (0)191 469 6111 24hr**Official Advisory Body Telephone No.:**
Advice for Doctors and Hospitals

+44 (0)844 892 0111

Email sdsfellinguk@akzonobel.com**SECTION 2: Hazards identification****2.1. Classification of the substance or mixture****Classification according to Regulation (EC) No 1272/2008**

Flam. Liq. 3;H226 Flammable liquid and vapour.

EUH066 Repeated exposure may cause skin dryness or cracking.

EUH208 Contains 2-Butanone oxime, Cobalt neodecanoate. May produce an allergic reaction.

Classification according to 67/548/EEC or 1999/45/EC.

R10 Flammable.

R66 Repeated exposure may cause skin dryness or cracking.

2.2. Label elements

Using the Toxicity Data listed in section 11 & 12 the product is labelled as follows.

According to Regulation (EC) No 1272/2008



Warning.

Contains:

H226 Flammable liquid and vapour.

EUH066 Repeated exposure may cause skin dryness or cracking.

EUH208 Contains 2-Butanone oxime, Cobalt neodecanoate. May produce an allergic reaction.

P102 Keep out of reach of children.

p260 Do not breathe mist / vapours / spray.

P271 Use only outdoors or in a well-ventilated area.

p280 Wear protective gloves / eye protection / face protection.

P333+313 If skin irritation or a rash occurs: Get medical advice / attention.

P501 Dispose of contents / container in accordance with local / national regulations.

According to 1999/45/EC

Contains:

R10 Flammable.

R66 Repeated exposure may cause skin dryness or cracking.

S2 Keep out of the reach of children.

S24 Avoid contact with skin.

S29 Do not empty into drains.

S46 If swallowed, seek medical advice immediately and show this container or label.

P. Phrases;

Contains 2-Butanone oxime, Cobalt neodecanoate. May produce an allergic reaction.

2.3. Other hazards

This product contains no PBT/vPvB chemicals.

SECTION 3: Composition/information on ingredients

If the product contains substances that present a health hazard within the meaning of the Dangerous Substances Directive 67/548/EC, or have occupational exposure limits detailed in EH40, these substances are listed below.

Ingredient/Chemical Designations	Weight %	67/548/EEC Classification	EC No. 1272/2008 Classification	Notes
Naphtha (petroleum), hydrotreated heavy CAS Number: 0064742-48-9 EC No. 265-150-3 Index No.: 649-327-00-6 REACH Reg. No.: 01-2119463258-33-xxxx	10 - < 25	R10 Xn;R65 R66	Asp. Tox. 1;H304 EUH066 Flam. Liq. 3;H226	H; P [1]

2-Butanone oxime CAS Number: 0000096-29-7 EC No. 202-496-6 Index No.: 616-014-00-0 REACH Reg. No.:	0 - < 1	Carc. Cat. 3;R40 Xn;R21 R43 Xi;R41	Carc. 2;H351 Acute Tox. 4;H312 Eye Dam. 1;H318 Skin Sens. 1;H317	[1]
Cobalt neodecanoate CAS Number: 0027253-31-2 EC No. 248-373-0 Index No.: REACH Reg. No.:	0 - < 1	Xn; R22, Xi; R38, R43, R10, N; R51/53	Asp. Tox. 1;H304, Acute Tox. 4;H302, Skin Sens. 1;H317, Flam. Liq. 3;H226, Aquatic Chronic 2;H411	[1]
Stoddard solvent CAS Number: 0008052-41-3 EC No. 232-489-3 Index No.: 649-345-00-4 REACH Reg. No.:	0 - < 1	Xn;R65	Asp. Tox. 1;H304	H; P [1][2]

[1] Substance classified with a health or environmental hazard.

[2] Substance with a workplace exposure limit.

[3] PBT-substance or vPvB-substance.

*The full texts of the phrases are shown in Section 16.

SECTION 4: First aid measures

4.1. Description of first aid measures

General

In all cases of doubt, or when symptoms persist, seek medical attention.

Never give anything by mouth to an unconscious person.

Inhalation

Remove to fresh air, keep patient warm and at rest. If breathing is irregular or stopped, give artificial respiration. If unconscious place in the recovery position and obtain immediate medical attention. Give nothing by mouth.

Skin

Remove contaminated clothing. Wash skin thoroughly with soap and water or use a recognised skin cleanser. Do NOT use solvents or thinners.

Eye

Irrigate copiously with clean fresh water for at least 10 minutes, holding the eyelids apart and seek medical attention.

Ingestion

If accidentally swallowed obtain immediate medical attention. Keep at rest. Do NOT induce vomiting.

4.2. Most important symptoms and effects, both acute and delayed

No data available

4.3. Indication of any immediate medical attention and special treatment needed

No data available

SECTION 5: Fire-fighting measures

5.1. Extinguishing media

Recommended extinguishing media; alcohol resistant foam, CO². powder, water spray.

Do not use; water jet.

5.2. Special hazards arising from the substance or mixture

Fire will produce dense black smoke. Decomposition products may include the following materials: carbon monoxide, carbon dioxide, smoke, oxides of nitrogen.

Avoid exposure and use breathing apparatus as appropriate.

5.3. Advice for fire-fighters

Cool closed containers exposed to fire by spraying them with water. Do not allow run off water and contaminants from fire fighting to enter drains or water courses.

SECTION 6: Accidental release measures

6.1. Personal precautions, protective equipment and emergency procedures

Remove sources of ignition, do not turn lights or unprotected electrical equipment on or off. In case of a major spill or spillage in a confined space evacuate the area and check that solvent vapour levels are below the Lower Explosive Limit before re-entering.

6.2. Environmental precautions

Do not allow spills to enter drains or watercourses.

6.3. Methods and material for containment and cleaning up

Ventilate the area and avoid breathing vapours. Take the personal protective measures listed in section 8.

Contain and absorb spillage with non-combustible materials e.g. sand, earth, vermiculite. Place in closed containers outside buildings and dispose of according to the Waste Regulations. (See section 13).

Clean, preferably with a detergent. Do not use solvents.

Do not allow spills to enter drains or watercourses.

If drains, sewers, streams or lakes are contaminated, inform the local water company immediately. In the case of contamination of rivers, streams or lakes the Environmental Protection Agency should also be informed.

SECTION 7: Handling and storage

7.1. Precautions for safe handling

Handling

This coating contains solvents. Solvent vapours are heavier than air and may spread along floors. Vapours may form explosive mixtures with air. Areas of storage, preparation and application should be ventilated to prevent the creation of flammable or explosive concentrations of vapour in air and avoid vapour concentrations higher than the occupational exposure limits.

In Storage

Handle containers carefully to prevent damage and spillage.

Naked flames and smoking should not be permitted in storage areas. It is recommended that fork lift trucks and electrical equipment are protected to the appropriate standard.

7.2. Conditions for safe storage, including any incompatibilities

Keep away from the following materials: oxidising agents, strong alkalis, strong acids.

Avoid skin and eye contact. Avoid inhalation of vapours and spray mists. Observe label precautions. Use personal protection as shown in section 8.

Smoking, eating and drinking should be prohibited in all preparation and application areas.

Never use pressure to empty a container; containers are not pressure vessels.

Store in a well ventilated, dry place away from sources of heat and direct sunlight.

Store on concrete or other impervious floor, preferably with bunding to contain any spillage. Do not stack more than 3 pallets high.

Keep container tightly closed. Containers which are opened must be carefully resealed and kept upright to

prevent leakage. Keep in the original container or one of the same material.

Prevent unauthorised access.

7.3. Specific end use(s)

There are no exposure scenarios, see details in section 1.

SECTION 8: Exposure controls/personal protection

8.1. Control parameters

The following workplace exposure limits have been established by the Health and Safety Executive as published in EH40.

Material	Short term (15 min. ave)		Long term (8hr TWA)		Comments
	ppm	mg/m ³	ppm	mg/m ³	
Naphtha (petroleum), hydrotreated heavy				1000	

For Key to entries in 'Comments' column see Section 16

DNEL/PNEC values

No Data Available

8.2. Exposure controls

Provide adequate ventilation. Where reasonably practicable this should be achieved by the use of local exhaust ventilation and good general extraction. If these are not sufficient to maintain concentrations of particulates and any vapour below occupational exposure limits suitable respiratory protection must be worn.

Eyeface protection

Wear safety eyewear, e.g. safety spectacles, goggles or visors to protect against the splash of liquids. Eyewear should meet the requirements of standard EN 166.

Skin protection

For prolonged or repeated handling, use the following type of gloves:

Recommended: foil.

Not recommended: butyl rubber, PVC.

Barrier creams may help to protect the exposed areas of the skin but should not be applied once exposure has occurred.

The recommendation for the type or types of glove to use when handling this product is based on information from the following source: www.esig.org

The user must check that the final choice of type of glove selected for handling this product is the most appropriate and takes into account the particular conditions of use, as included in the user's risk assessment.

Other

Overalls which cover the body, arms and legs should be worn. Skin should not be exposed. Barrier creams may help to protect areas which are difficult to cover such as the face and neck. They should however not be applied once exposure has occurred. Petroleum jelly based types such as Vaseline should not be used. All parts of the body should be washed after contact.

Respiratory protection

If workers are exposed to concentrations above the exposure limit they must use the appropriate, certified respirators. For maximum protection when spraying this product it is recommended that a multi layer combination type filter, such as ABEK1, is used. In confined spaces use compressed air or fresh air respiratory equipment.

Thermal hazards
No Data Available

SECTION 9: Physical and chemical properties

Appearance	Light Coloured Liquid
Odour	Smell of Solvent
Odour threshold	Not Measured
pH	Not Measured
Melting point / freezing point (°C)	Not Measured
Initial boiling point and boiling range (°C)	137
Flash point (°C)	35
Evaporation rate (Ether = 1)	Not Measured
Flammability (solid, gas)	Not Applicable
Upper/lower flammability or explosive limits	Lower Explosive Limit: Not Measured Upper Explosive Limit: Not Measured
Vapour pressure (Pa)	Not Measured
Vapour density	Heavier than air.
Relative density	1.41
Solubility(ies)	Immiscible
Partition coefficient n-octanol/water (Log Kow)	Not Measured
Auto-ignition temperature (°C)	Not Measured
Decomposition temperature	Not Measured
Viscosity (cSt)	220

9.2. Other information
No further information

SECTION 10: Stability and reactivity

10.1. Reactivity
No data available

10.2. Chemical stability
Stable under recommended storage and handling conditions (see section 7). When exposed to high temperatures may produce hazardous decomposition products such as carbon monoxide, carbon dioxide, oxides of nitrogen and smoke.

Keep away from oxidising agents, strongly alkaline and strongly acid materials in order to avoid possible exothermic reactions.

10.3. Possibility of hazardous reactions
May react exothermically with: oxidising agents, strong alkalis, strong acids.

10.4. Conditions to avoid
Stable under recommended storage and handling conditions (see section 7).

10.5. Incompatible materials
Keep away from the following materials: oxidising agents, strong alkalis, strong acids.

10.6. Hazardous decomposition products
Fire will produce dense black smoke. Decomposition products may include the following materials: carbon monoxide, carbon dioxide, smoke, oxides of nitrogen.

Avoid exposure and use breathing apparatus as appropriate.

SECTION 11: Toxicological information

Acute toxicity

Exposure to solvent vapour concentrations from the component solvents in excess of the stated occupational exposure limits may result in adverse health effects such as mucous membrane and respiratory system irritation and adverse effects on the kidneys, liver and central nervous system. Symptoms include headache, nausea, dizziness, fatigue, muscular weakness, drowsiness and in extreme cases, loss of consciousness.

Repeated or prolonged contact with the preparation may cause removal of natural fat from the skin resulting in dryness, irritation and possible non-allergic contact dermatitis. Solvents may also be absorbed through the skin. Splashes of liquid in the eyes may cause irritation and soreness with possible reversible damage.

The preparation has been assessed using the Acute Toxicity Data listed below, and classified for toxicological hazards accordingly. See section 2 for details.

Ingredient	Oral LD50, mg/kg	Skin LD50, mg/kg	Inhalation Vapour LD50, mg/L/4hr	Inhalation Dust/Mist LD50, mg/L/4hr
2-Butanone oxime - (96-29-7)	930.00, Rat	2,000.00, Rabbit	20.00, Rat	Not Available
Cobalt neodecanoate - (27253-31-2)	900.00, Rat	Not Available	Not Available	Not Available
Naphtha (petroleum), hydrotreated heavy - (64742-48-9)	5,000.00, Rat	3,160.00, Rabbit	Not Available	Not Available
Stoddard solvent - (8052-41-3)	Not Available	Not Available	Not Available	Not Available

Classification	Category	Hazard Description
Acute toxicity (oral)	Not Classified	Not Applicable
Acute toxicity (dermal)	Not Classified	Not Applicable
Acute toxicity (inhalation)	Not Classified	Not Applicable
Skin corrosion/irritation	Not Classified	Not Applicable
Serious eye damage/irritation	Not Classified	Not Applicable
Respiratory sensitization	Not Classified	Not Applicable
Skin sensitization	Not Classified	Not Applicable
Germ cell mutagenicity	Not Classified	Not Applicable
Carcinogenicity	Not Classified	Not Applicable
Reproductive toxicity	Not Classified	Not Applicable
STOT-single exposure	Not Classified	Not Applicable
STOT-repeated exposure	Not Classified	Not Applicable
Aspiration hazard	Not Classified	Not Applicable

SECTION 12: Ecological information

12.1. Toxicity

The preparation has been assessed following the conventional method of the Dangerous Preparations Directive 1999/45/EC and is not classified as dangerous for the environment

There are no data available on the product itself.

Aquatic Ecotoxicity

12.2. Persistence and degradability

12.3. Bioaccumulative potential

12.4. Mobility in soil

12.5. Results of PBT and vPvB assessment

12.6. Other adverse effects

SECTION 13: Disposal considerations

Do not allow into drains or water courses. Wastes and emptied containers should be disposed of in accordance with regulations made under the Control of Pollution Act and the Environmental Protection Act.

The European Waste Catalogue Classification of this product, when disposed of as waste is 08 01 11 Waste paint and varnish containing organic solvents or other dangerous substances. If mixed with other wastes this code may no longer apply and the appropriate code should be assigned. For further information contact your local waste authority.

SECTION 14: Transport information

ADR/RID/ADN UN1263 Paint, 3, III

ICAO/IATA Air class 3 Sub Class -

14.4. Packing group

III

14.5. Environmental hazards

ADR/RID/ADN Environmentally Hazardous: No

IMDG Marine Pollutant: No

14.6. Special precautions for user

No further information

14.7. Transport in bulk according to Annex II of MARPOL73/78 and the IBC Code

Not Applicable

SECTION 15: Regulatory information

EU Legislation

REGULATION (EC) No 1272/2008 OF THE EUROPEAN PARLIAMENT AND OF THE COUNCIL on classification, labelling and packaging of substances and mixtures, amending and repealing Directives 67/548/EEC and 1999/45/EC, and amending Regulation (EC) No 1907/2006.

REGULATION (EC) No 1907/2006 OF THE EUROPEAN PARLIAMENT AND OF THE COUNCIL concerning the Registration, Evaluation, Authorisation and Restriction of Chemicals (REACH), establishing a European Chemicals Agency, amending Directive 1999/45/EC and repealing Council Regulation (EEC) No 793/93 and Commission Regulation (EC) No 1488/94 as well as Council Directive 76/769/EEC and Commission Directives 91/155/EEC, 93/67/EEC, 93/105/EC and 2000/21/EC

National Legislation

UKSI 2009 No. 716 CHEMICALS (HAZARD INFORMATION AND PACKAGING FOR SUPPLY) REGULATIONS 2009.

SECTION 16: Other information

IMPORTANT NOTE: the information contained in this data sheet (as may be amended from time to time) is not intended to be exhaustive and is presented in good faith and believed to be correct as of the date on which it is prepared. It is the user's responsibility to verify that this data sheet is current prior to using the product to which it relates.

Persons using the information must make their own determinations as to the suitability of the relevant product for their purposes prior to use. Where those purposes are other than as specifically recommended in this safety data sheet, then the user uses the product at their own risk.

MANUFACTURER'S DISCLAIMER: the conditions, methods and factors affecting the handling, storage, application, use and disposal of the product are not under the control and knowledge of the manufacturer. Therefore the manufacturer does not assume responsibility for any adverse events which may occur in the handling, storage, application, use, misuse or disposal of the product and, so far as permitted by applicable law, the manufacturer expressly disclaims liability for any and all loss, damages and/or expenses arising out of or in any way connected to the storage, handling, use or disposal of the product. Safe handling, storage, use and disposal are the responsibility of the users. Users must comply with all applicable health and safety laws.

Unless we have agreed to the contrary, all products are supplied by us subject to our standard terms and conditions of business, which include limitations of liability. Please make sure to refer to these and / or the relevant agreement which you have with AkzoNobel (or its affiliate, as the case may be).

© AkzoNobel

The information in this Health & Safety Data Sheet is required pursuant to EC Regulation 1907(2006) and the Chemicals (Hazard Information & Packaging for Supply) Regulations 2009.

Key to 'Comments' column in Section 8.

(+) There is a risk of absorption through unbroken skin.

(C) Capable of causing cancer and/or heritable genetic damage.

(R) Suppliers recommended limit.

(S) Capable of causing occupational asthma.

The full text of the R, H & EUH phrases appearing in section 3 is:

H226 Flammable liquid and vapour.

H302 Harmful if swallowed.

H304 May be fatal if swallowed and enters airways.

H312 Harmful in contact with skin.

H317 May cause an allergic skin reaction.

H318 Causes serious eye damage.

H351 Suspected of causing cancer.

H411 Toxic to aquatic life with long lasting effects.

EUH066 Repeated exposure may cause skin dryness or cracking.

R10 Flammable.

R21 Harmful in contact with skin.

R22 Harmful if swallowed.

R38 Irritating to skin.

R40 Limited evidence of a carcinogenic effect.

R41 Risk of serious damage to eyes.

R43 May cause sensitisation by skin contact.

R51/53 Toxic to aquatic organisms, may cause long-term adverse effects in the aquatic environment.

R65 Harmful: may cause lung damage if swallowed.

R66 Repeated exposure may cause skin dryness or cracking.

Xn Harmful.

The following sections have changed since the previous revision.

SECTION 12: Ecological information

End of document



Your attention is drawn to the disclaimer on the Product Data Sheet which with this Safety Data Sheet and the package labelling comprise an integral information system about this product. Copies of the Product Data Sheet are available from International Paint on request or from our Internet sites : www.yachtpaint.com , www.international-marine.com, www.international-pc.com