Product Information Sheet

COMMISSION DELEGATED REGULATION (EU) 2019/2015 with regard to energy labelling of light sources

sources								
Supplier's name	e or trade mark:	Schmidt Security To	ols					
Supplier's address: Service, Lise-Meitner-Str. 5, 52511 Geilenkirchen, DE								
Model identifier: WLB5000								
Type of light source:								
Lighting technology used:		LED	Non-directional or directional:	NDLS				
Light source cap-type (or other electric interface)		Other						
Mains or non-mains:		NMLS	Connected light source (CLS):	Nein				
Colour-tuneable light source:		Nein	Envelope:	-				
High luminance light source:		Nein						
Anti-glare shield:		Nein	Dimmable:	No				
Product parameters								
Parameter		Value	Parameter .	Value				
General product parameters:								
Energy consumption in on- mode (kWh/1000 h), rounded up to the nearest integer		36	Energy efficiency class	E				
Useful luminous flux (фuse), indicating if it refers to the flux in a sphere (360°), in a wide cone (120°) or in a narrow cone (90°)		5 000 in Sphere (360°)	Correlated colour temperature, rounded to the nearest 100 K, or the range of correlated colour temperatures, rounded to the nearest 100 K, that can be set	6 500				
On-mode power (P _{on}), expressed in W		36,0	Standby power (P _{sb}), expressed in W and rounded to the second decimal	0,00				
Networked standby power (P _{net}) for CLS, expressed in W and rounded to the second decimal		-	Colour rendering index, rounded to the nearest integer, or the range of CRI-values that can be set	84				
Outer	Height	1 450	Spectral power	See image				
dimensions without	Width	180	distribution in the	in last page				
without	Depth	180		 				

separate control gear, lighting control parts and non- lighting control parts, if any (millimetre)			range 250 nm to 800 nm, at full-load			
Claim of equivalent power ^(a)		-	If yes, equivalent power (W)	-		
			Chromaticity	0,308		
			coordinates (x and y)	0,336		
Parameters for LED and OLED light sources:						
R9 colour rendering index value		33	Survival factor	0,90		
the lumen maintenance factor		0,96				

(a)'-': not applicable; (b)'-': not applicable;

Spectral power distribution

