

Model name

A12FT UL2 (Outdoor unit) / A12FT NSF (Indoor unit)

Function (indicate if present)	
cooling	Y
heating	Y

If the function includes heating: Indicate the heating season the information relates to. Indicated values should relate to one heating season at a time. Include at least the heating season 'Average'.
Average (mandatory) Y
Warmer (if designated) Y
Colder (if designated) N

Item	symbol	value	unit
Design load			
cooling	Pdesignc	3,5	kW
heating / Average	Pdesignh	2,7	kW
heating / Warmer	Pdesignh	1,5	kW
heating / Colder	Pdesignh	x,x	kW

Declared capacity* for cooling, at indoor temperature 27(19)°C and outdoor temperature Tj

Tj=35°C	Pdc	3,50	kW
Tj=30°C	Pdc	2,58	kW
Tj=25°C	Pdc	1,66	kW
Tj=20°C	Pdc	1,04	kW

Declared capacity* for heating / Average climate, at indoor temperature 20°C and outdoor temperature Td

Tj=-7°C	Pdh	2,39	kW
Tj=2°C	Pdh	1,46	kW
Tj=7°C	Pdh	0,98	kW
Tj=12°C	Pdh	1,10	kW
Tj=bivalent temperature	Pdh	2,70	kW
Tj=operating limit	Pdh	2,70	kW

Declared capacity* for heating / Warmer climate, at indoor temperature 20°C and outdoor temperature Tj

Tj=2°C	Pdh	1,50	kW
Tj=7°C	Pdh	0,98	kW
Tj=12°C	Pdh	1,10	kW
Tj=bivalent temperature	Pdh	1,50	kW
Tj=operating limit	Pdh	1,50	kW

Declared capacity* for heating / Colder climate, at indoor temperature 20°C and outdoor temperature Tj

Tj=-7°C	Pdh	x,x	kW
Tj=2°C	Pdh	x,x	kW
Tj=7°C	Pdh	x,x	kW
Tj=12°C	Pdh	x,x	kW
Tj=bivalent temperature	Pdh	x,x	kW
Tj=operating limit	Pdh	x,x	kW
Tj=-15°C	Pdh	x,x	kW

Declared Energy efficiency ratio* for cooling, at indoor temperature 27(19)°C and outdoor temperature Tj

Tj=35°C	EERd	3,33	-
Tj=30°C	EERd	5,13	-
Tj=25°C	EERd	7,94	-
Tj=20°C	EERd	12,40	-

Declared Coefficient of performance* for heating / Average climate, at indoor temperature 20°C and outdoor temperature Tj

Tj=-7°C	COPd	2,80	-
Tj=2°C	COPd	4,15	-
Tj=7°C	COPd	4,50	-
Tj=12°C	COPd	6,00	-
Tj=bivalent temperature	COPd	2,45	-
Tj=operating limit	COPd	2,45	-

Declared Coefficient of performance* / Warmer climate, at indoor temperature 20°C and outdoor temperature Tj

Tj=2°C	COPd	4,09	-
Tj=7°C	COPd	4,50	-
Tj=12°C	COPd	6,00	-
Tj=bivalent temperature	COPd	4,09	-
Tj=operating limit	COPd	4,09	-

Declared Coefficient of performance* / Colder climate, at indoor temperature 20°C and outdoor temperature Tj

Tj=-7°C	Pdh	x,x	kW
Tj=2°C	Pdh	x,x	kW
Tj=7°C	Pdh	x,x	kW
Tj=12°C	Pdh	x,x	kW
Tj=bivalent temperature	Pdh	x,x	kW
Tj=operating limit	Pdh	x,x	kW
Tj=-15°C	Pdh	x,x	kW

Declared Coefficient of performance* / Colder climate, at indoor temperature 20°C and outdoor temperature Tj

Tj=-7°C	COPd	x,x	-
Tj=2°C	COPd	x,x	-
Tj=7°C	COPd	x,x	-
Tj=12°C	COPd	x,x	-
Tj=bivalent temperature	COPd	x,x	-
Tj=operating limit	COPd	x,x	-
Tj=-15°C	COPd	x,x	-

Bivalent temperature

heating / Average	Tbiv	-10	°C
heating / Warmer	Tbiv	2	°C
heating / Colder	Tbiv	x	°C

Operating limit temperature

heating / Average	Tol	-10	°C
heating / Warmer	Tol	2	°C
heating / Colder	Tol	x	°C

Cycling interval capacity

for cooling	Pcyc	x,x	kW
for heating	Pcyc	x,x	kW

Cycling interval efficiency

for cooling	EERcyc	x,x	-
for heating	COPcyc	x,x	-

Degradation co-efficient

Cdc	0,25	-
-----	------	---

Degradation co-efficient

Cdh	0,25	-
-----	------	---

Electric power input in power modes other than 'active mode'

off mode	P _{OFF}	0,003	kW
standby mode	P _{SB}	0,003	kW
thermostat-off mode	P _{TO}	0,02	kW
crankcase heater mode	P _{CK}	0	kW

Annual electricity consumption

cooling	Q _{CE}	186	kWh/a
heating / Average	Q _{HE}	945	kWh/a
heating / Warmer	Q _{HE}	457	kWh/a
heating / Colder	Q _{HE}	xx	kWh/a

Capacity control (indicate one of three options)

fixed	N	
staged	N	
variable	Y	

Other items

Sound power level (indoor/outdoor)	L _{WA}	60 / 65	dB(A)
Global warming potential	GWP	675	kgCO ₂ eq.
Rated air flow (indoor/outdoor)	-	600 / 2100	m ³ /h

Contact details for obtaining more information

Christianna PAPAZAHARIOU
Internal communicator - Energy & environment regulations expert
LG Electronics
Paris Nord II – 117 avenue des Nations
BP 59372 Villepinte – 95942 Roissy CDG Cedex
chris.papazahariou@lge.com
Tel. +33 1 49 89 57 41, +33 6 83 077 455

*= For staged capacity units, two values divided by a slash ('/') will be declared in each box in the section "Declared capacity of the unit" and "declared EER/COP" of the unit.
**= If default Cd=0,25 is chosen then (results from) cycling tests are not required. Otherwise either the heating or cooling cycling test value is required.

