

Information to identify the model(s) to which the information relates to:				If function includes heating: Indicate the heating season the information relates to. Indicated values should relate to one heating season at a time. Include at least the heating season 'Average'.				
Indoor unit model name		SRK25ZSX-WF		Average(mandatory)		Yes		
Outdoor unit model name		SRC25ZSX-W		Warmer(if designated)		Yes		
Function(indicate if present)				Colder(if designated)				
cooling		Yes						
heating		Yes				No		
Item symbol value unit				Item symbol value class				
Design load				Seasonal efficiency and energy efficiency class				
cooling		Pdesignc	2.50	kW	cooling	SEER	10.30	A+++
heating / Average		Pdesignh	3.00	kW	heating / Average	SCOP/A	5.20	A+++
heating / Warmer		Pdesignh	4.20	kW	heating / Warmer	SCOP/W	6.60	A+++
heating / Colder		Pdesignh	-	kW	heating / Colder	SCOP/C	-	-
				unit				
Declared capacity at outdoor temperature Tdesignh				Back up heating capacity at outdoor temperature Tdesignh				
heating / Average (-10°C)		Pdc	3.00	kW	heating / Average (-10°C)	elbu	0	kW
heating / Warmer (2°C)		Pdc	4.20	kW	heating / Warmer (2°C)	elbu	0	kW
heating / Colder (-22°C)		Pdc	-	kW	heating / Colder (-22°C)	elbu	-	kW
Declared capacity for cooling, at indoor temperature 27(19)°C and outdoor temperature Tj				Declared energy efficiency ratio, at indoor temperature 27(19)°C and outdoor temperature Tj				
Tj=35°C		Pdc	2.50	kW	Tj=35°C	EERd	5.68	-
Tj=30°C		Pdc	1.84	kW	Tj=30°C	EERd	8.75	-
Tj=25°C		Pdc	1.27	kW	Tj=25°C	EERd	14.10	-
Tj=20°C		Pdc	1.40	kW	Tj=20°C	EERd	20.40	-
Declared capacity for heating / Average season, at indoor temperature 20°C and outdoor temperature Tj				Declared coefficient of performance / Average season, at indoor temperature 20°C and outdoor temperature Tj				
Tj=-7°C		Pdh	2.61	kW	Tj=-7°C	COPd	3.15	-
Tj=2°C		Pdh	1.59	kW	Tj=2°C	COPd	5.30	-
Tj=7°C		Pdh	1.03	kW	Tj=7°C	COPd	6.58	-
Tj=12°C		Pdh	0.96	kW	Tj=12°C	COPd	8.30	-
Tj=bivalent temperature		Pdh	3.00	kW	Tj=bivalent temperature	COPd	2.69	-
Tj=operating limit		Pdh	3.00	kW	Tj=operating limit	COPd	2.69	-
Declared capacity for heating / Warmer season, at indoor temperature 20°C and outdoor temperature Tj				Declared coefficient of performance / Warmer season, at indoor temperature 20°C and outdoor temperature Tj				
Tj=2°C		Pdh	4.20	kW	Tj=2°C	COPd	3.30	-
Tj=7°C		Pdh	2.70	kW	Tj=7°C	COPd	5.90	-
Tj=12°C		Pdh	1.20	kW	Tj=12°C	COPd	8.31	-
Tj=bivalent temperature		Pdh	4.20	kW	Tj=bivalent temperature	COPd	3.30	-
Tj=operating limit		Pdh	4.20	kW	Tj=operating limit	COPd	3.30	-
Declared capacity for heating / Colder season, at indoor temperature 20°C and outdoor temperature Tj				Declared coefficient of performance / Colder season, at indoor temperature 20°C and outdoor temperature Tj				
Tj=-7°C		Pdh	-	kW	Tj=-7°C	COPd	-	-
Tj=2°C		Pdh	-	kW	Tj=2°C	COPd	-	-
Tj=7°C		Pdh	-	kW	Tj=7°C	COPd	-	-
Tj=12°C		Pdh	-	kW	Tj=12°C	COPd	-	-
Tj=bivalent temperature		Pdh	-	kW	Tj=bivalent temperature	COPd	-	-
Tj=operating limit		Pdh	-	kW	Tj=operating limit	COPd	-	-
Tj=-15°C		Pdh	-	kW	Tj=-15°C	COPd	-	-
Bivalent temperature				Operating limit temperature				
heating / Average		Tbiv	-10	°C	heating / Average	Tol	-10	°C
heating / Warmer		Tbiv	2	°C	heating / Warmer	Tol	2	°C
heating / Colder		Tbiv	-	°C	heating / Colder	Tol	-	°C
Cycling interval capacity				Cycling interval efficiency				
for cooling		Pcycc	-	kW	for cooling	EERcyc	-	-
for heating		Pcyhc	-	kW	for heating	COPcyc	-	-
Degradation coefficient				Degradation coefficient				
cooling		Cdc	0.25	-	heating	Cdh	0.25	-
Electric power input in power modes other than 'active mode'				Annual electricity consumption				
off mode		Poff	4	W	cooling	Qce	85	kWh/a
standby mode		Psb	4	W	heating / Average	Qhe	808	kWh/a
thermostat-off mode		Pto(cooling)	11	W	heating / Warmer	Qhe	891	kWh/a
crankcase heater mode		Pto(heating)	14	W	heating / colder	Qhe	-	kWh/a
crankcase heater mode		Pck	0	W				
Capacity control(indicate one of three options)				Other items				
fixed		No		Sound power level(indoor)	Lwa	55	dB(A)	
staged		No		Sound power level(outdoor)	Lwa	57	dB(A)	
variable		Yes		Global warming potential	GWP	675	kgCO2eq.	
				Rated air flow(indoor)	-	732	m3/h	
				Rated air flow(outdoor)	-	1860	m3/h	
Contact details for obtaining more information		Name and address of the manufacturer or of its authorised representative.						
		MHIAE SERVICES B.V. Herikerbergweg 238, Luna ArenA, 1101 CM Amsterdam, Netherlands P.O.Box 23393 1100 DW Amsterdam, Netherlands						