Information to identify the model(s) to which the information relates to:	
Indoor unit model name	**SRK50ZS-WFT x 2 units**
Outdoor unit model name	**SCM60ZS-W**

If function includes heating: Indicate the heating season the information relates to. Indicated values should relate to one heating season at a time. Include at least the heating season 'Average'.

Function(indicate if present)	
cooling	**Yes**
heating	**Yes**

Average(mandatory)	**Yes**
Warmer(if designated)	**Yes**
Colder(if designated)	**No**

Item	symbol	value	unit
Design load			
cooling	Pdesignc	**6.00**	kW
heating / Average	Pdesignh	**4.80**	kW
heating / Warmer	Pdesignh	**6.40**	kW
heating / Colder	Pdesignh	**-**	kW
Declared capacity at outdoor temperature Tdesignh			
heating / Average (−10℃)	Pdc	**4.80**	kW
heating / Warmer (2℃)	Pdc	**6.40**	kW
heating / Colder (−22℃)	Pdc	**-**	kW
Declared capacity for cooling, at indoor temperature 27(19)℃ and outdoor temperature Tj			
Tj=35℃	Pdc	**6.00**	kW
Tj=30℃	Pdc	**4.40**	kW
Tj=25℃	Pdc	**2.80**	kW
Tj=20℃	Pdc	**2.65**	kW
Declared capacity for heating / Average season, at indoor temperature 20℃ and outdoor temperature Tj			
Tj=−7℃	Pdh	**4.10**	kW
Tj=2℃	Pdh	**2.60**	kW
Tj=7℃	Pdh	**1.65**	kW
Tj=12℃	Pdh	**1.95**	kW
Tj=bivalent temperature	Pdh	**4.80**	kW
Tj=operating limit	Pdh	**4.35**	kW
Declared capacity for heating / Warmer season, at indoor temperature 20℃ and outdoor temperature Tj			
Tj=2℃	Pdh	**6.40**	kW
Tj=7℃	Pdh	**4.05**	kW
Tj=12℃	Pdh	**1.95**	kW
Tj=bivalent temperature	Pdh	**6.40**	kW
Tj=operating limit	Pdh	**4.35**	kW
Declared capacity for heating / Colder season, at indoor temperature 20℃ and outdoor temperature Tj			
Tj=−7℃	Pdh	**-**	kW
Tj=2℃	Pdh	**-**	kW
Tj=7℃	Pdh	**-**	kW
Tj=12℃	Pdh	**-**	kW
Tj=bivalent temperature	Pdh	**-**	kW
Tj=operating limit	Pdh	**-**	kW
Tj=−15℃	Pdh	**-**	kW
Bivalent temperature			
heating / Average	Tbiv	**-10**	℃
heating / Warmer	Tbiv	**2**	℃
heating / Colder	Tbiv	**-**	℃
Cycling interval capacity			
for cooling	Pcycc	**-**	kW
for heating	Pcych	**-**	kW
Degradation coefficient			
cooling	Cdc	**0.25**	–
Electric power input in power modes other than 'active mode'			
off mode	Poff	**15**	W
standby mode	Psb	**15**	W
thermostat-off mode	Pto(cooling)	**30**	W
	Pto(heating)	**40**	W
crankcase heater mode	Pck	**0**	W

Item	symbol	value	class
Seasonal efficiency and energy efficiency class			
cooling	SEER	**6.80**	A++
heating / Average	SCOP/A	**4.50**	A+
heating / Warmer	SCOP/W	**6.10**	A+++
heating / Colder	SCOP/C	**-**	-
			unit
Back up heating capacity at outdoor temperature Tdesignh			
heating / Average (−10℃)	elbu	**0**	kW
heating / Warmer (2℃)	elbu	**0**	kW
heating / Colder (−22℃)	elbu	**-**	kW
Declared energy efficiency ratio, at indoor temperature 27(19)℃ and outdoor temperature Tj			
Tj=35℃	EERd	**3.11**	–
Tj=30℃	EERd	**5.58**	–
Tj=25℃	EERd	**10.17**	–
Tj=20℃	EERd	**13.01**	–
Declared coefficient of performance / Average season, at indoor temperature 20℃ and outdoor temperature Tj			
Tj=−7℃	COPd	**3.09**	–
Tj=2℃	COPd	**4.45**	–
Tj=7℃	COPd	**5.51**	–
Tj=12℃	COPd	**7.60**	–
Tj=bivalent temperature	COPd	**2.47**	–
Tj=operating limit	COPd	**2.28**	–
Declared coefficient of performance / Warmer season, at indoor temperature 20℃ and outdoor temperature Tj			
Tj=2℃	COPd	**2.95**	–
Tj=7℃	COPd	**5.65**	–
Tj=12℃	COPd	**7.60**	–
Tj=bivalent temperature	COPd	**2.95**	–
Tj=operating limit	COPd	**2.28**	–
Declared coefficient of performance / Colder season, at indoor temperature 20℃ and outdoor temperature Tj			
Tj=−7℃	COPd	**-**	–
Tj=2℃	COPd	**-**	–
Tj=7℃	COPd	**-**	–
Tj=12℃	COPd	**-**	–
Tj=bivalent temperature	COPd	**-**	–
Tj=operating limit	COPd	**-**	–
Tj=−15℃	COPd	**-**	–
Operating limit temperature			
heating / Average	Tol	**-15**	℃
heating / Warmer	Tol	**-15**	℃
heating / Colder	Tol	**-**	℃
Cycling interval efficiency			
for cooling	EERcyc	**-**	–
for heating	COPcyc	**-**	–
Degradation coefficient			
heating	Cdh	**0.25**	–
Annual electricity consumption			
cooling	Qce	**309**	kWh/a
heating / Average	Qhe	**1494**	kWh/a
heating / Warmer	Qhe	**1469**	kWh/a
heating / colder	Qhe	**-**	kWh/a

Capacity control(indicate one of three options)	
fixed	**No**
staged	**No**
variable	**Yes**

Other items			
Sound power level(indoor)	Lwa	* **59**	dB(A)
Sound power level(outdoor)	Lwa	**63**	dB(A)
Global warming potential	GWP	**675**	kgCO2eq.
Rated air flow(indoor)	–	**786**	m3/h
Rated air flow(outdoor)	–	**2460**	m3/h

* The sound power level indicated is the highest value among that of connected indoor units.

Contact details for obtaining more information	Name and address of the manufacturer or of its authorised representative.
	MHIAE SERVICES B.V. Herikerbergweg 238, Luna ArenA, 1101 CM Amsterdam, Netherlands P.O.Box 23393 1100 DW Amsterdam, Netherlands