Information to identify the model(s) to which the information relates to:	
Indoor unit model name	SRK20ZS-WF, SRK50ZS-WF
Outdoor unit model name	SCM60ZS-W

If function includes heating: Indicate the heating season the information relates to. Indicated values should relate to one heating season at a time. Include at least the heating season 'Average'.

Function(indicate if present)	
cooling	Yes
heating	Yes

Average(mandatory)	Yes
Warmer(if designated)	Yes
Colder(if designated)	No

Item	symbol	value	unit
Design load			
cooling	Pdesignc	6.00	kW
heating / Average	Pdesignh	4.80	kW
heating / Warmer	Pdesignh	6.40	kW
heating / Colder	Pdesignh	-	kW

Item	symbol	value	class
Seasonal efficiency and energy efficiency class			
cooling	SEER	6.80	A++
heating / Average	SCOP/A	4.50	A+
heating / Warmer	SCOP/W	6.10	A+++
heating / Colder	SCOP/C	-	-

Declared capacity at outdoor temperature Tdesignh			
heating / Average (−10°C)	Pdc	4.80	kW
heating / Warmer (2°C)	Pdc	6.40	kW
heating / Colder (−22°C)	Pdc	-	kW

Back up heating capacity at outdoor temperature Tdesignh			
heating / Average (−10°C)	elbu	0	kW
heating / Warmer (2°C)	elbu	0	kW
heating / Colder (−22°C)	elbu	-	kW

Declared capacity for cooling, at indoor temperature 27(19)°C and outdoor temperature Tj			
Tj=35°C	Pdc	6.00	kW
Tj=30°C	Pdc	4.40	kW
Tj=25°C	Pdc	2.80	kW
Tj=20°C	Pdc	2.65	kW

Declared energy efficiency ratio, at indoor temperature 27(19)°C and outdoor temperature Tj			
Tj=35°C	EERd	3.11	–
Tj=30°C	EERd	5.58	–
Tj=25°C	EERd	10.17	–
Tj=20°C	EERd	13.01	–

Declared capacity for heating / Average season, at indoor temperature 20°C and outdoor temperature Tj			
Tj=−7°C	Pdh	4.10	kW
Tj=2°C	Pdh	2.60	kW
Tj=7°C	Pdh	1.65	kW
Tj=12°C	Pdh	1.95	kW
Tj=bivalent temperature	Pdh	4.80	kW
Tj=operating limit	Pdh	4.35	kW

Declared coefficient of performance / Average season, at indoor temperature 20°C and outdoor temperature Tj			
Tj=−7°C	COPd	3.09	–
Tj=2°C	COPd	4.45	–
Tj=7°C	COPd	5.51	–
Tj=12°C	COPd	7.60	–
Tj=bivalent temperature	COPd	2.47	–
Tj=operating limit	COPd	2.28	–

Declared capacity for heating / Warmer season, at indoor temperature 20°C and outdoor temperature Tj			
Tj=2°C	Pdh	6.40	kW
Tj=7°C	Pdh	4.05	kW
Tj=12°C	Pdh	1.95	kW
Tj=bivalent temperature	Pdh	6.40	kW
Tj=operating limit	Pdh	4.35	kW

Declared coefficient of performance / Warmer season, at indoor temperature 20°C and outdoor temperature Tj			
Tj=2°C	COPd	2.95	–
Tj=7°C	COPd	5.65	–
Tj=12°C	COPd	7.60	–
Tj=bivalent temperature	COPd	2.95	–
Tj=operating limit	COPd	2.28	–

Declared capacity for heating / Colder season, at indoor temperature 20°C and outdoor temperature Tj			
Tj=−7°C	Pdh	-	kW
Tj=2°C	Pdh	-	kW
Tj=7°C	Pdh	-	kW
Tj=12°C	Pdh	-	kW
Tj=bivalent temperature	Pdh	-	kW
Tj=operating limit	Pdh	-	kW
Tj=−15°C	Pdh	-	kW

Declared coefficient of performance / Colder season, at indoor temperature 20°C and outdoor temperature Tj			
Tj=−7°C	COPd	-	–
Tj=2°C	COPd	-	–
Tj=7°C	COPd	-	–
Tj=12°C	COPd	-	–
Tj=bivalent temperature	COPd	-	–
Tj=operating limit	COPd	-	–
Tj=−15°C	COPd	-	–

Bivalent temperature			
heating / Average	Tbiv	-10	°C
heating / Warmer	Tbiv	2	°C
heating / Colder	Tbiv	-	°C

Operating limit temperature			
heating / Average	Tol	-15	°C
heating / Warmer	Tol	-15	°C
heating / Colder	Tol	-	°C

Cycling interval capacity			
for cooling	Pcycc	-	kW
for heating	Pcych	-	kW

Cycling interval efficiency			
for cooling	EERcyc	-	–
for heating	COPcyc	-	–

Degradation coefficient			
cooling	Cdc	0.25	–

Degradation coefficient			
heating	Cdh	0.25	–

Electric power input in power modes other than 'active mode'			
off mode	Poff	15	W
standby mode	Psb	15	W
thermostat-off mode	Pto(cooling)	30	W
	Pto(heating)	40	W
crankcase heater mode	Pck	0	W

Annual electricity consumption			
cooling	Qce	309	kWh/a
heating / Average	Qhe	1494	kWh/a
heating / Warmer	Qhe	1469	kWh/a
heating / colder	Qhe	-	kWh/a

Capacity control(indicate one of three options)	
fixed	No
staged	No
variable	Yes

Other items			
Sound power level(indoor)	Lwa	* 59	dB(A)
Sound power level(outdoor)	Lwa	63	dB(A)
Global warming potential	GWP	675	kgCO2eq.
Rated air flow(indoor)	–	786	m3/h
Rated air flow(outdoor)	–	2460	m3/h

* The sound power level indicated is the highest value among that of connected indoor units.

Contact details for obtaining more information	Name and address of the manufacturer or of its authorised representative.
	MHIAE SERVICES B.V. Herikerbergweg 238, Luna ArenA, 1101 CM Amsterdam, Netherlands P.O.Box 23393 1100 DW Amsterdam, Netherlands