

### SECTION 1: Identification of the substance/mixture and of the company/undertaking

#### 1.1. Product identifier

Product form : Mixture  
Trade name : Nanolex Si3D HD  
UFI : JW70-R08Y-C00S-PEAE  
Product group : Coatings and paints, thinners, paint removers

#### 1.2. Relevant identified uses of the substance or mixture and uses advised against

##### 1.2.1. Relevant identified uses

Main use category : Industrial use, Professional use, Consumer use

##### 1.2.2. Uses advised against

No additional information available

#### 1.3. Details of the supplier of the safety data sheet

Infinitec GmbH  
Matzenberg, 171  
D-66115 Saarbrücken  
Deutschland  
T +49(0)68190677655  
[b.mazreku@infinitec-gmbh.de](mailto:b.mazreku@infinitec-gmbh.de) - [www.infinitec-technology.de](http://www.infinitec-technology.de)

#### 1.4. Emergency telephone number

Emergency number : +49(0)613119240

### SECTION 2: Hazards identification

#### 2.1. Classification of the substance or mixture

##### Classification according to Regulation (EC) No. 1272/2008 [CLP]

Acute toxicity (oral), Category 4	H302
Acute toxicity (inhalation:dust,mist) Category 4	H332
Skin corrosion/irritation, Category 1, Sub-Category 1B	H314
Serious eye damage/eye irritation, Category 1	H318
Full text of H- and EUH-statements: see section 16	

##### Adverse physicochemical, human health and environmental effects

Harmful if inhaled. Harmful if swallowed. Causes severe skin burns and eye damage. Causes serious eye damage.

#### 2.2. Label elements

##### Labelling according to Regulation (EC) No. 1272/2008 [CLP]

Hazard pictograms (CLP) :



Signal word (CLP) : Danger  
Contains : 2-butoxyethyl acetate; butylglycol acetate; ORGANISCHE POLYSILAZAN  
Hazard statements (CLP) : H302+H332 - Harmful if swallowed or if inhaled.  
H314 - Causes severe skin burns and eye damage.  
Precautionary statements (CLP) : P101 - If medical advice is needed, have product container or label at hand.  
P102 - Keep out of reach of children.  
P260 - Do not breathe spray, vapours, gas, mist, fume, dust.  
P264 - Wash hands, forearms and face thoroughly after handling.  
P270 - Do not eat, drink or smoke when using this product.

# Nanolex Si3D HD

## Safety Data Sheet

according to the REACH Regulation (EC) 1907/2006 amended by Regulation (EU) 2020/878

P271 - Use only outdoors or in a well-ventilated area.  
P280 - Wear protective clothing, eye protection, face protection, protective gloves.  
P301+P312 - IF SWALLOWED: Call a POISON CENTER, doctor if you feel unwell.  
P501 - Dispose of contents and container to authorised waste disposal facility.  
EUH-statements : EUH208 - Contains . May produce an allergic reaction.

### 2.3. Other hazards

Contains no PBT/vPvB substances  $\geq 0.1\%$  assessed in accordance with REACH Annex XIII

The mixture does not contain substance(s) included in the list established in accordance with Article 59(1) of REACH for having endocrine disrupting properties, or is not identified as having endocrine disrupting properties in accordance with the criteria set out in Commission Delegated Regulation (EU) 2017/2100 or Commission Regulation (EU) 2018/605 at a concentration equal to or greater than 0,1 %

## SECTION 3: Composition/information on ingredients

### 3.1. Substances

Not applicable

### 3.2. Mixtures

Name	Product identifier	%	Classification according to Regulation (EC) No. 1272/2008 [CLP]
2-butoxyethyl acetate; butylglycol acetate substance with national workplace exposure limit(s) (DE)	CAS-No.: 112-07-2 EC-No.: 203-933-3 EC Index-No.: 607-038-00-2	50 – 85	Acute Tox. 4 (Oral), H302 (ATE=500 mg/kg bodyweight) Acute Tox. 4 (Dermal), H312 (ATE=1100 mg/kg bodyweight) Acute Tox. 4 (Inhalation), H332 (ATE=1.5 mg/l/4h)
ORGANISCHE POLYSILAZAN	CAS-No.: 475645-84-2	10 – 20	Flam. Liq. 2, H225 Water-react. 3, H261 Acute Tox. 4 (Oral), H302 (ATE=300 mg/kg bodyweight) Skin Corr. 1B, H314 Eye Dam. 1, H318 Aquatic Chronic 3, H412
N-BUTYL ACETATE substance with national workplace exposure limit(s) (DE)	CAS-No.: 123-86-4 EC-No.: 204-658-1 EC Index-No.: 607-025-00-1	1 – 20	Flam. Liq. 3, H226 STOT SE 3, H336 EUH066
toluene substance with national workplace exposure limit(s) (DE)	CAS-No.: 108-88-3 EC-No.: 203-625-9 EC Index-No.: 601-021-00-3	< 1	Flam. Liq. 2, H225 Repr. 2, H361d Asp. Tox. 1, H304 STOT RE 2, H373 Skin Irrit. 2, H315 STOT SE 3, H336
methyl methacrylate; methyl 2-methylprop-2-enoate; methyl 2-methylpropenoate substance with national workplace exposure limit(s) (DE)	CAS-No.: 80-62-6 EC-No.: 201-297-1 EC Index-No.: 607-035-00-6	< 1	Flam. Liq. 2, H225 STOT SE 3, H335 Skin Irrit. 2, H315 Skin Sens. 1, H317
n-butyl acrylate substance with national workplace exposure limit(s) (DE)	CAS-No.: 141-32-2 EC-No.: 205-480-7 EC Index-No.: 607-062-00-3	< 1	Flam. Liq. 3, H226 Eye Irrit. 2, H319 STOT SE 3, H335 Skin Irrit. 2, H315 Skin Sens. 1, H317

Full text of H- and EUH-statements: see section 16

# Nanolex Si3D HD

## Safety Data Sheet

according to the REACH Regulation (EC) 1907/2006 amended by Regulation (EU) 2020/878

### SECTION 4: First aid measures

#### 4.1. Description of first aid measures

First-aid measures general	: Call a physician immediately.
First-aid measures after inhalation	: Remove person to fresh air and keep comfortable for breathing. Call a poison center or a doctor if you feel unwell.
First-aid measures after skin contact	: Rinse skin with water/shower. Take off immediately all contaminated clothing. Call a physician immediately.
First-aid measures after eye contact	: Rinse cautiously with water for several minutes. Remove contact lenses, if present and easy to do. Continue rinsing. Call a physician immediately.
First-aid measures after ingestion	: Rinse mouth. Do not induce vomiting. Call a physician immediately.

#### 4.2. Most important symptoms and effects, both acute and delayed

Symptoms/effects after skin contact	: Burns.
Symptoms/effects after eye contact	: Serious damage to eyes.
Symptoms/effects after ingestion	: Burns.

#### 4.3. Indication of any immediate medical attention and special treatment needed

Treat symptomatically.

### SECTION 5: Firefighting measures

#### 5.1. Extinguishing media

Suitable extinguishing media	: Water spray. Dry powder. Foam. Carbon dioxide.
------------------------------	--

#### 5.2. Special hazards arising from the substance or mixture

Hazardous decomposition products in case of fire	: Toxic fumes may be released.
--	--------------------------------

#### 5.3. Advice for firefighters

Protection during firefighting	: Do not attempt to take action without suitable protective equipment. Self-contained breathing apparatus. Complete protective clothing.
--------------------------------	--

### SECTION 6: Accidental release measures

#### 6.1. Personal precautions, protective equipment and emergency procedures

##### 6.1.1. For non-emergency personnel

Emergency procedures	: Ventilate spillage area. Avoid contact with skin and eyes. Do not breathe dust/fume/gas/mist/vapours/spray.
----------------------	---

##### 6.1.2. For emergency responders

Protective equipment	: Do not attempt to take action without suitable protective equipment. For further information refer to section 8: "Exposure controls/personal protection".
----------------------	---

#### 6.2. Environmental precautions

Avoid release to the environment.

#### 6.3. Methods and material for containment and cleaning up

Methods for cleaning up	: Take up liquid spill into absorbent material.
Other information	: Dispose of materials or solid residues at an authorized site.

#### 6.4. Reference to other sections

For further information refer to section 13.

# Nanolex Si3D HD

## Safety Data Sheet

according to the REACH Regulation (EC) 1907/2006 amended by Regulation (EU) 2020/878

### SECTION 7: Handling and storage

#### 7.1. Precautions for safe handling

- Precautions for safe handling : Use only outdoors or in a well-ventilated area. Avoid contact with skin and eyes. Do not breathe dust/fume/gas/mist/vapours/spray. Wear personal protective equipment.
- Hygiene measures : Wash contaminated clothing before reuse. Do not eat, drink or smoke when using this product. Always wash hands after handling the product.

#### 7.2. Conditions for safe storage, including any incompatibilities

- Storage conditions : Store locked up. Store in a well-ventilated place. Keep cool.

#### 7.3. Specific end use(s)

No additional information available

### SECTION 8: Exposure controls/personal protection

#### 8.1. Control parameters

##### 8.1.1 National occupational exposure and biological limit values

No additional information available

##### 8.1.2. Recommended monitoring procedures

No additional information available

##### 8.1.3. Air contaminants formed

No additional information available

##### 8.1.4. DNEL and PNEC

No additional information available

##### 8.1.5. Control banding

No additional information available

#### 8.2. Exposure controls

##### 8.2.1. Appropriate engineering controls

**Appropriate engineering controls:**

Ensure good ventilation of the work station.

##### 8.2.2. Personal protection equipment

**Personal protective equipment symbol(s):**



###### 8.2.2.1. Eye and face protection

**Eye protection:**

Safety glasses

###### 8.2.2.2. Skin protection

**Skin and body protection:**

Wear suitable protective clothing

**Hand protection:**

Protective gloves

###### 8.2.2.3. Respiratory protection

**Respiratory protection:**

[In case of inadequate ventilation] wear respiratory protection.

# Nanolex Si3D HD

## Safety Data Sheet

according to the REACH Regulation (EC) 1907/2006 amended by Regulation (EU) 2020/878

### 8.2.2.4. Thermal hazards

No additional information available

### 8.2.3. Environmental exposure controls

#### Environmental exposure controls:

Avoid release to the environment.

## SECTION 9: Physical and chemical properties

### 9.1. Information on basic physical and chemical properties

Physical state	: Liquid
Colour	: Not available
Odour	: Not available
Odour threshold	: Not available
Melting point	: Not applicable
Freezing point	: Not available
Boiling point	: Not available
Flammability	: Non flammable.
Explosive limits	: Not available
Lower explosion limit	: Not available
Upper explosion limit	: Not available
Flash point	: 62 °C
Auto-ignition temperature	: Not available
Decomposition temperature	: Not available
pH	: Not available
Viscosity, kinematic	: Not available
Viscosity, dynamic	: < 100 mPa·s
Solubility	: Not available
Partition coefficient n-octanol/water (Log Kow)	: Not available
Vapour pressure	: Not available
Vapour pressure at 50°C	: Not available
Density	: Not available
Relative density	: Not available
Relative vapour density at 20°C	: Not available
Particle characteristics	: Not applicable

### 9.2. Other information

#### 9.2.1. Information with regard to physical hazard classes

No additional information available

#### 9.2.2. Other safety characteristics

No additional information available

## SECTION 10: Stability and reactivity

### 10.1. Reactivity

The product is non-reactive under normal conditions of use, storage and transport.

### 10.2. Chemical stability

Stable under normal conditions.

### 10.3. Possibility of hazardous reactions

No dangerous reactions known under normal conditions of use.

### 10.4. Conditions to avoid

None under recommended storage and handling conditions (see section 7).

# Nanolex Si3D HD

## Safety Data Sheet

according to the REACH Regulation (EC) 1907/2006 amended by Regulation (EU) 2020/878

### 10.5. Incompatible materials

No additional information available

### 10.6. Hazardous decomposition products

Under normal conditions of storage and use, hazardous decomposition products should not be produced.

## SECTION 11: Toxicological information

### 11.1. Information on hazard classes as defined in Regulation (EC) No 1272/2008

Acute toxicity (oral) : Harmful if swallowed.  
Acute toxicity (dermal) : Not classified  
Acute toxicity (inhalation) : Harmful if inhaled.

#### Nanolex Si3D HD

ATE CLP (oral)	579.151 mg/kg bodyweight
ATE CLP (dust,mist)	2.83 mg/l/4h

#### 2-butoxyethyl acetate; butylglycol acetate (112-07-2)

LD50 oral rat	1880 mg/kg
LD50 dermal rabbit	1480 mg/kg
LC50 Inhalation - Rat	> 3.91 mg/l

#### ORGANISCHE POLYSILAZAN (475645-84-2)

LD50 oral rat	300 – 2000 mg/kg
---------------	------------------

#### toluene (108-88-3)

LD50 oral rat	5580 mg/kg
LD50 dermal rabbit	12267 mg/kg
LC50 Inhalation - Rat	20 mg/l

#### methyl methacrylate; methyl 2-methylprop-2-enoate; methyl 2-methylpropenoate (80-62-6)

LD50 oral rat	7900 mg/kg
LD50 dermal rabbit	> 5000 mg/kg
LC50 Inhalation - Rat	29.8 mg/l

#### n-butyl acrylate (141-32-2)

LD50 oral rat	3150 mg/kg
LD50 dermal rabbit	> 2000 – 3024 mg/kg
LC50 Inhalation - Rat	10.3 mg/l

#### N-BUTYL ACETATE (123-86-4)

LD50 oral rat	10800 mg/kg
LD50 dermal rabbit	> 17600 mg/kg
LC50 Inhalation - Rat	1.85 mg/l/4h

Skin corrosion/irritation : Causes severe skin burns.  
Serious eye damage/irritation : Causes serious eye damage.  
Respiratory or skin sensitisation : Not classified  
Germ cell mutagenicity : Not classified  
Carcinogenicity : Not classified  
Reproductive toxicity : Not classified

# Nanolex Si3D HD

## Safety Data Sheet

according to the REACH Regulation (EC) 1907/2006 amended by Regulation (EU) 2020/878

STOT-single exposure : Not classified

### toluene (108-88-3)

STOT-single exposure : May cause drowsiness or dizziness.

### methyl methacrylate; methyl 2-methylprop-2-enoate; methyl 2-methylpropenoate (80-62-6)

STOT-single exposure : May cause respiratory irritation.

### n-butyl acrylate (141-32-2)

STOT-single exposure : May cause respiratory irritation.

### N-BUTYL ACETATE (123-86-4)

STOT-single exposure : May cause drowsiness or dizziness.

STOT-repeated exposure : Not classified

### toluene (108-88-3)

STOT-repeated exposure : May cause damage to organs through prolonged or repeated exposure.

Aspiration hazard : Not classified

### 2-butoxyethyl acetate; butylglycol acetate (112-07-2)

Viscosity, kinematic : 1.921 mm<sup>2</sup>/s

## 11.2. Information on other hazards

No additional information available

## SECTION 12: Ecological information

### 12.1. Toxicity

Ecology - general : Before neutralisation, the product may represent a danger to aquatic organisms.

Hazardous to the aquatic environment, short-term (acute) : Not classified

Hazardous to the aquatic environment, long-term (chronic) : Not classified

Not rapidly degradable

### 2-butoxyethyl acetate; butylglycol acetate (112-07-2)

LC50 - Fish [1]	28.3 mg/l
EC50 - Crustacea [1]	37 mg/l DIN 38412
EC50 72h - Algae [1]	1570 mg/l ISO 8692

### toluene (108-88-3)

LC50 - Fish [1]	5.8 (0 – 0) mg/l
EC50 96h - Algae [1]	≥ 0 mg/l
NOEC chronic fish	1.4 mg/l

### methyl methacrylate; methyl 2-methylprop-2-enoate; methyl 2-methylpropenoate (80-62-6)

LC50 - Fish [1]	> 100 mg/l
LC50 - Fish [2]	233 mg/l
EC50 - Other aquatic organisms [1]	69 mg/l
EC50 72h - Algae [1]	110 mg/l
NOEC chronic fish	9.4 mg/l

# Nanolex Si3D HD

## Safety Data Sheet

according to the REACH Regulation (EC) 1907/2006 amended by Regulation (EU) 2020/878

<b>n-butyl acrylate (141-32-2)</b>	
LC50 - Fish [1]	5.2 mg/l
LC50 - Fish [2]	2.1 mg/l
EC50 - Other aquatic organisms [1]	8.2 mg/l
EC50 72h - Algae [1]	2.65 mg/l
<b>N-BUTYL ACETATE (123-86-4)</b>	
LC50 - Fish [1]	81 mg/l

### 12.2. Persistence and degradability

No additional information available

### 12.3. Bioaccumulative potential

<b>2-butoxyethyl acetate; butylglycol acetate (112-07-2)</b>	
Partition coefficient n-octanol/water (Log Pow)	1.51 (20°C)

### 12.4. Mobility in soil

No additional information available

### 12.5. Results of PBT and vPvB assessment

No additional information available

### 12.6. Endocrine disrupting properties

No additional information available

### 12.7. Other adverse effects

No additional information available

## SECTION 13: Disposal considerations

### 13.1. Waste treatment methods

Waste treatment methods	: Dispose of contents/container in accordance with licensed collector's sorting instructions.
HP Code	: HP3 - "Flammable:" <ul style="list-style-type: none"><li>– flammable liquid waste: liquid waste having a flash point below 60 °C or waste gas oil, diesel and light heating oils having a flash point &gt; 55 °C and ≤ 75 °C;</li><li>– flammable pyrophoric liquid and solid waste: solid or liquid waste which, even in small quantities, is liable to ignite within five minutes after coming into contact with air;</li><li>– flammable solid waste: solid waste which is readily combustible or may cause or contribute to fire through friction;</li><li>– flammable gaseous waste: gaseous waste which is flammable in air at 20 °C and a standard pressure of 101.3 kPa;</li><li>– water reactive waste: waste which, in contact with water, emits flammable gases in dangerous quantities;</li><li>– other flammable waste: flammable aerosols, flammable self-heating waste, flammable organic peroxides and flammable self-reactive waste.</li></ul>
	HP6 - "Acute Toxicity:" waste which can cause acute toxic effects following oral or dermal administration, or inhalation exposure.
	HP8 - "Corrosive:" waste which on application can cause skin corrosion.

## SECTION 14: Transport information






In accordance with ADR / IMDG / IATA / ADN / RID



# Nanolex Si3D HD

## Safety Data Sheet

according to the REACH Regulation (EC) 1907/2006 amended by Regulation (EU) 2020/878

ADR	IMDG	IATA	ADN	RID
<b>14.1. UN number or ID number</b>				
UN 1760	UN 1760	UN 1760	UN 1760	UN 1760
<b>14.2. UN proper shipping name</b>				
CORROSIVE LIQUID, N.O.S. (2-butoxyethyl acetate; butylglycol acetate ; ORGANISCHE POLYSILAZAN)	CORROSIVE LIQUID, N.O.S. (2-butoxyethyl acetate; butylglycol acetate ; ORGANISCHE POLYSILAZAN)	Corrosive liquid, n.o.s. (2-butoxyethyl acetate; butylglycol acetate ; ORGANISCHE POLYSILAZAN)	CORROSIVE LIQUID, N.O.S. (2-butoxyethyl acetate; butylglycol acetate ; ORGANISCHE POLYSILAZAN)	CORROSIVE LIQUID, N.O.S. (2-butoxyethyl acetate; butylglycol acetate ; ORGANISCHE POLYSILAZAN)
<b>Transport document description</b>				
UN 1760 CORROSIVE LIQUID, N.O.S. (2-butoxyethyl acetate; butylglycol acetate ; ORGANISCHE POLYSILAZAN), 8, III, (E)	UN 1760 CORROSIVE LIQUID, N.O.S. (2-butoxyethyl acetate; butylglycol acetate ; ORGANISCHE POLYSILAZAN), 8, III	UN 1760 Corrosive liquid, n.o.s. (2-butoxyethyl acetate; butylglycol acetate ; ORGANISCHE POLYSILAZAN), 8, III	UN 1760 CORROSIVE LIQUID, N.O.S. (2-butoxyethyl acetate; butylglycol acetate ; ORGANISCHE POLYSILAZAN), 8, III	UN 1760 CORROSIVE LIQUID, N.O.S. (2-butoxyethyl acetate; butylglycol acetate ; ORGANISCHE POLYSILAZAN), 8, III
<b>14.3. Transport hazard class(es)</b>				
8	8	8	8	8
				
<b>14.4. Packing group</b>				
III	III	III	III	III
<b>14.5. Environmental hazards</b>				
Dangerous for the environment: No	Dangerous for the environment: No Marine pollutant: No	Dangerous for the environment: No	Dangerous for the environment: No	Dangerous for the environment: No
No supplementary information available				

### 14.6. Special precautions for user

#### Overland transport

Classification code (ADR) : C9  
Special provisions (ADR) : 274  
Limited quantities (ADR) : 1I  
Excepted quantities (ADR) : E2  
Packing instructions (ADR) : P001, IBC02  
Mixed packing provisions (ADR) : MP15  
Portable tank and bulk container instructions (ADR) : T11  
Portable tank and bulk container special provisions (ADR) : TP2, TP27  
Tank code (ADR) : L4BN  
Vehicle for tank carriage : AT  
Transport category (ADR) : 2  
Hazard identification number (Kemler No.) : 80  
Orange plates :



Tunnel restriction code (ADR) : E

# Nanolex Si3D HD

## Safety Data Sheet

according to the REACH Regulation (EC) 1907/2006 amended by Regulation (EU) 2020/878

### Transport by sea

Special provisions (IMDG)	: 274
Limited quantities (IMDG)	: 1 L
Excepted quantities (IMDG)	: E2
Packing instructions (IMDG)	: P001
IBC packing instructions (IMDG)	: IBC02
Tank instructions (IMDG)	: T11
Tank special provisions (IMDG)	: TP2, TP27
EmS-No. (Fire)	: F-A
EmS-No. (Spillage)	: S-B
Stowage category (IMDG)	: B
Stowage and handling (IMDG)	: SW2
Properties and observations (IMDG)	: Causes burns to skin, eyes and mucous membranes.

### Air transport

PCA Excepted quantities (IATA)	: E2
PCA Limited quantities (IATA)	: Y840
PCA limited quantity max net quantity (IATA)	: 0.5L
PCA packing instructions (IATA)	: 851
PCA max net quantity (IATA)	: 1L
CAO packing instructions (IATA)	: 855
CAO max net quantity (IATA)	: 30L
Special provisions (IATA)	: A3, A803
ERG code (IATA)	: 8L

### Inland waterway transport

Classification code (ADN)	: C9
Special provisions (ADN)	: 274
Limited quantities (ADN)	: 1 L
Excepted quantities (ADN)	: E2
Carriage permitted (ADN)	: T
Equipment required (ADN)	: PP, EP
Number of blue cones/lights (ADN)	: 0

### Rail transport

Classification code (RID)	: C9
Special provisions (RID)	: 274
Limited quantities (RID)	: 1L
Excepted quantities (RID)	: E2
Packing instructions (RID)	: P001, IBC02
Mixed packing provisions (RID)	: MP15
Portable tank and bulk container instructions (RID)	: T11
Portable tank and bulk container special provisions (RID)	: TP2, TP27
Tank codes for RID tanks (RID)	: L4BN
Transport category (RID)	: 2
Colis express (express parcels) (RID)	: CE6
Hazard identification number (RID)	: 80

### 14.7. Maritime transport in bulk according to IMO instruments

Not applicable

## SECTION 15: Regulatory information

### 15.1. Safety, health and environmental regulations/legislation specific for the substance or mixture

#### 15.1.1. EU-Regulations

##### REACH Annex XVII (Restriction List)

Contains no substance(s) listed on REACH Annex XVII (Restriction Conditions)

# Nanolex Si3D HD

## Safety Data Sheet

according to the REACH Regulation (EC) 1907/2006 amended by Regulation (EU) 2020/878

### REACH Annex XIV (Authorisation List)

Contains no substance(s) listed on REACH Annex XIV (Authorisation List)

### REACH Candidate List (SVHC)

Contains no substance(s) listed on the REACH Candidate List

### PIC Regulation (Prior Informed Consent)

Contains no substance(s) listed on the PIC list (Regulation EU 649/2012 concerning the export and import of hazardous chemicals)

### POP Regulation (Persistent Organic Pollutants)

Contains no substance(s) listed on the POP list (Regulation EU 2019/1021 on persistent organic pollutants)

### Ozone Regulation (1005/2009)

Contains no substance(s) listed on the Ozone Depletion list (Regulation EU 1005/2009 on substances that deplete the ozone layer)

### Explosives Precursors Regulation (2019/1148)

Contains no substance(s) listed on the Explosives Precursors list (Regulation EU 2019/1148 on the marketing and use of explosives precursors)

### Drug Precursors Regulation (273/2004)

Contains substance(s) listed on the Drug Precursors list (Regulation EC 273/2004 on the manufacture and the placing on market of certain substances used in the illicit manufacture of narcotic drugs and psychotropic substances)

Name	CN designation	CAS-No.	CN code	Category	Threshold	Annex
Toluene		108-88-3	2902 30 00	Category 3		Annex I

### 15.1.2. National regulations

No additional information available

## 15.2. Chemical safety assessment

No chemical safety assessment has been carried out

## SECTION 16: Other information

### Abbreviations and acronyms:

ADN	European Agreement concerning the International Carriage of Dangerous Goods by Inland Waterways
ADR	European Agreement concerning the International Carriage of Dangerous Goods by Road
ATE	Acute Toxicity Estimate
BCF	Bioconcentration factor
BLV	Biological limit value
BOD	Biochemical oxygen demand (BOD)
COD	Chemical oxygen demand (COD)
DMEL	Derived Minimal Effect level
DNEL	Derived-No Effect Level
EC-No.	European Community number
EC50	Median effective concentration
EN	European Standard
IARC	International Agency for Research on Cancer
IATA	International Air Transport Association
IMDG	International Maritime Dangerous Goods
LC50	Median lethal concentration
LD50	Median lethal dose

# Nanolex Si3D HD

## Safety Data Sheet

according to the REACH Regulation (EC) 1907/2006 amended by Regulation (EU) 2020/878

Abbreviations and acronyms:	
LOAEL	Lowest Observed Adverse Effect Level
NOAEC	No-Observed Adverse Effect Concentration
NOAEL	No-Observed Adverse Effect Level
NOEC	No-Observed Effect Concentration
OECD	Organisation for Economic Co-operation and Development
OEL	Occupational Exposure Limit
PBT	Persistent Bioaccumulative Toxic
PNEC	Predicted No-Effect Concentration
RID	Regulations concerning the International Carriage of Dangerous Goods by Rail
SDS	Safety Data Sheet
STP	Sewage treatment plant
ThOD	Theoretical oxygen demand (ThOD)
TLM	Median Tolerance Limit
VOC	Volatile Organic Compounds
CAS-No.	Chemical Abstract Service number
N.O.S.	Not Otherwise Specified
vPvB	Very Persistent and Very Bioaccumulative
ED	Endocrine disrupting properties

Full text of H- and EUH-statements:	
Acute Tox. 4 (Dermal)	Acute toxicity (dermal), Category 4
Acute Tox. 4 (Inhalation)	Acute toxicity (inhal.), Category 4
Acute Tox. 4 (Oral)	Acute toxicity (oral), Category 4
Aquatic Chronic 3	Hazardous to the aquatic environment – Chronic Hazard, Category 3
Asp. Tox. 1	Aspiration hazard, Category 1
EUH066	Repeated exposure may cause skin dryness or cracking.
EUH208	Contains . May produce an allergic reaction.
Eye Dam. 1	Serious eye damage/eye irritation, Category 1
Eye Irrit. 2	Serious eye damage/eye irritation, Category 2
Flam. Liq. 2	Flammable liquids, Category 2
Flam. Liq. 3	Flammable liquids, Category 3
H225	Highly flammable liquid and vapour.
H226	Flammable liquid and vapour.
H261	In contact with water releases flammable gases.
H302	Harmful if swallowed.
H304	May be fatal if swallowed and enters airways.
H312	Harmful in contact with skin.
H314	Causes severe skin burns and eye damage.
H315	Causes skin irritation.

# Nanolex Si3D HD

## Safety Data Sheet

according to the REACH Regulation (EC) 1907/2006 amended by Regulation (EU) 2020/878

Full text of H- and EUH-statements:	
H317	May cause an allergic skin reaction.
H318	Causes serious eye damage.
H319	Causes serious eye irritation.
H332	Harmful if inhaled.
H335	May cause respiratory irritation.
H336	May cause drowsiness or dizziness.
H361d	Suspected of damaging the unborn child.
H373	May cause damage to organs through prolonged or repeated exposure.
H412	Harmful to aquatic life with long lasting effects.
Repr. 2	Reproductive toxicity, Category 2
Skin Corr. 1B	Skin corrosion/irritation, Category 1, Sub-Category 1B
Skin Irrit. 2	Skin corrosion/irritation, Category 2
Skin Sens. 1	Skin sensitisation, Category 1
STOT RE 2	Specific target organ toxicity – Repeated exposure, Category 2
STOT SE 3	Specific target organ toxicity – Single exposure, Category 3, Narcosis
Water-react. 3	Substances and Mixtures which, in contact with water, emit flammable gases, Category 3

Classification and procedure used to derive the classification for mixtures according to Regulation (EC) 1272/2008 [CLP]:		
Acute Tox. 4 (Oral)	H302	Calculation method
Acute Tox. 4 (Inhalation:dust,mist)	H332	Calculation method
Skin Corr. 1B	H314	Calculation method
Eye Dam. 1	H318	Calculation method

The classification complies with : ATP 12

Safety Data Sheet (SDS), EU

This information is based on our current knowledge and is intended to describe the product for the purposes of health, safety and environmental requirements only. It should not therefore be construed as guaranteeing any specific property of the product.